

AMENDMENT NO. 2

Page 8

Sub-clause 3.4.2, Table I

- Group 0. In columns 2 and 3 respectively, above "Visual examination" and "4.1" add "High surge current 5)" and "4.17".
- Add a footnote 5) as follows: "For solid electrolyte capacitors only and if prescribed by the detail specification."

Page 9

Sub-clause 3.4.2, Table II

Amend the following test groups as indicated:

- Group 0. In the first column, above "4.1 Visual examination" add: "4.17 High surge current*".
- Add a footnote at the bottom of the page as follows:
 "* For solid electrolyte capacitors only and if prescribed by the detail specification."

Page 11 Table II (continued)

- Group 1, Sub-clause 4.10.7
 - 1) Transfer this sub-clause to the end of the group after 4.10.8
 - 2) Add as Performance requirement: "Maximum leakage: ..."
 - 3) Renumber the present sub-clause
 "4.10.7" to "4.10.8" and
 "4.10.8" to "4.10.7"

IS QC 300200 : 2000
IEC QC 300200 (1982)

Page 12 Table II (continued)

- Group 2, Performance requirements

Change for Long-life grade capacitors the capacitance change $\frac{\Delta C}{C}$ from " $\leq 5 \%$ " to " $\leq 8 \%$ ".

Page 14 Table II (continued)

- Group 5, Sub-clause 4.15

1) Insert between Steps 2 and 3 new Step 3 as follows:

Step 3: 20 °C (if applicable)

2) Renumber the present Steps 3 and 4 to Steps 4 and 5

3) Add a new Step 6: 20 °C (if applicable)

4) Add for the new Steps 3 and 6 the conditions of test

- Leakage current
- Capacitance
- Tangent of loss angle
- Impedance (if applicable)

5) The applicability of the Steps 3 and 6 shall be given in the detail specification.

- Group 5, Sub-clause 4.16.3

Add after Visual examination in:

3rd column:
"Leakage current"

5th column:
" $\leq$ initial limit"

Page 16

- Sub-clause 3.5.3

Replace "capacitance" in the second sentence by:

"... for Sub-families 1 and 2: leakage current and for Sub-family 3: capacitance."

- Table IIIA

- In column 1, above "A1" insert "A0***".

- On the same line in column 4 insert: "100 %".

- At the bottom of the page add a footnote as follows:

"*** High surge current test, for solid electrolyte capacitors only and if required by the detail specification."

Page 17Sub-clause 4.2.1.1

Replace in first sentence: "the rated voltage" by "the voltage appropriate to the test temperature".

Sub-clause 4.2.1.2

Delete the second part of the sentence:

"the value of these 12,5 μ A respectively".

Page 20Sub-clause 4.3.2

Replace title by: "Tests U_{a1} , U_b and U_c applicable".

Page 22Sub-clause 4.7.1

Replace in first line after the table:

"frequency range" by "severity (frequency/amplitude or acceleration/duration)".

Page 24Sub-clause 4.10.7

Renumber this sub-clause to "4.10.8"

Sub-clause 4.10.8

- Renumber this sub-clause to "4.10.7"

- Replace the text by:

"The capacitors shall be kept under standard atmospheric conditions for testing for 1 to 2 h and shall then be inspected and measured and meet the requirements shown in Table II."

Page 25Sub-clause 4.12.2 a)

Change the last sentence to read:

"The impedance seen from the terminals of each capacitor shall not exceed 3 Ω ."

Page 27

Add a new clause 4.19 as follows:

- 4.19 High surge current (for solid electrolyte capacitors only and if required by the detail specification)

See 4.39 of IEC Publication 384-1 with the following details:

4.19.1 Initial measurements

Not required.

4.19.2 Measurements and requirements

Final measurements and requirements are those for the subsequent tests in Group 0 or in the blank detail specification or Group A, as appropriate.