

**AMENDMENT NO. 1 SEPTEMBER 2008
TO
IS 12798 : 1989 HOUSEHOLD SEWING MACHINES —
FLYWHEELS — SPECIFICATION**

(Page 2, Fig. 2):

- a) Substitute ' $\varnothing 74 \pm 0.5$ ' for ' $\varnothing 76.2 \pm 0.2$ '.
- b) Substitute ' $\varnothing 143 \pm 1$ ' for ' $\varnothing 143.5$ '.
- c) Substitute ' 19 ± 0.1 ' for ' 18.4 ± 0.1 '.

(Page 3, Fig. 3):

- a) Substitute ' $\varnothing 74 \pm 0.5$ ' for ' $\varnothing 76.2 \pm 0.2$ '.
- b) Substitute 'R7.5' for 'R7.6'.
- c) Substitute ' $\varnothing 114 \pm 0.5$ ' for ' $\varnothing 113.5$ '.
- d) Substitute ' 15.1 ± 0.1 ' for ' 15.2 ± 0.1 '.

(Page 3, clause 7.3) — Substitute the following for the existing matter:

'The outside surface of rim of flywheel shall be bright chrome plated with a minimum combined (Nickel and Chrome) plating thickness of 10 microns. The plated surface shall be free of any burrs, blemishes, stains, yellow marks and pit marks.'

(Page 4, Fig. 4):

- a) Substitute ' $\varnothing 74 \pm 0.5$ ' for ' $\varnothing 76.2 \pm 0.2$ '.
- b) Substitute ' $\varnothing 118 \pm 0.5$ ' for ' $\varnothing 117.5$ '.
- c) Substitute ' 13 ± 0.25 ' for ' $\varnothing 12.95.0^\circ$ '.
- d) Substitute ' $\varnothing 22 \pm 0.5$ ' for ' $\varnothing 14.28$ '.

(ME 29)