

**AMENDMENT NO. 2 JUNE 2026**  
**TO**  
**IS 12817 : 2020 STAINLESS STEEL BUTT HINGES — SPECIFICATION**  
*( Third Revision )*

*(Page 1, clause 2)* — Substitute the following for the existing *(see also Amendment No. 1)*:

**‘2 REFERENCES**

The standards given below contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of these standards:

| <i>IS No.</i>                       | <i>Title</i>                                                                          |
|-------------------------------------|---------------------------------------------------------------------------------------|
| IS 4905 : 2015/<br>ISO 24153 : 2019 | Random sampling and randomization procedures <i>(first revision)</i>                  |
| IS 5528 : 2024/<br>ISO 9227 : 2022  | Corrosion tests in artificial atmospheres — Salt spray tests <i>(second revision)</i> |
| IS 6528 : 2024                      | Stainless steel wire — Specification <i>(second revision)</i>                         |
| IS 6760 : 1972                      | Specification for slotted countersunk head wood screws                                |
| IS 6911 : 2026                      | Stainless steel plate, sheet and strip — Specification <i>(third revision)</i>        |

*(Page 1, clause 3)* — Substitute the following for the existing:

**‘3 CONSTRUCTION AND TYPE**

**3.1** Based on construction, stainless steel butt hinges shall be classified as follows:

- a) Plain joint hinges;
- b) Washer hinges;
- c) Bearing hinges; and
- d) Welded hinges.

**3.2** Further, stainless steel butt hinges shall be of the following types:

- a) Light weight (narrow) hinges *(see Table 1)*;
- b) Light weight unequal flap hinges *(see Table 2)*;
- c) Medium weight hinges *(see Table 3)*;
- d) Medium weight (narrow) hinges *(see Table 4)*;
- e) Heavy weight unequal flap hinges *(see Table 5)*; and
- f) Heavy weight hinges *(see Table 6)*.’

*(Page 1, clause 4)* — Insert the following at the end:

**‘4.2** Other stainless steel materials may also be used as agreed between the manufacturer and the purchaser. However, the Indian Standard and grade of that material shall be declared by the manufacturer.’

*(Page 1, clause 6)* — Insert the following at the end:

**Price Group 2**

## Amendment No. 2 to IS 12817 : 2020

**6.3** In each type of stainless steel butt hinges (*see 3.2*), any other dimensions, that is, combination of length, breadth, thickness of flap, and diameter of pin, may also be manufactured as agreed between the manufacturer and the purchaser. However, the thickness of the flap and the diameter of the hinge pin shall not be less than the nearest higher size of the hinge in the same type. Also, in such cases, the number of screw holes, holes for screw number and positions of holes shall be declared by the manufacturer.

**6.3.1** The tolerances on any other dimensions shall be as follows:

- a) Length:  $\pm 0.5$  mm; and
- b) Breadth:  $\pm 1.0$  mm.

**6.3.2** For thickness of flap, where specified as '*C Min.*' from Table 1 to Table 6, a manufacturing tolerance of  $-0.05$  mm shall be allowed on the finished product with respect to the specified value.

NOTE — For example, in Table 1, where the thickness of flap (*C Min.*) is specified as 1.20 mm for size 50, the minimum acceptable thickness on the finished product shall be 1.15 mm.'

[Page 2, Table 1, clause reference, see also Amendment No. 1] — Substitute '(Clauses 3.2, 6.2, 6.3.2, 7.2, 7.3, 7.4 and 7.4.1)' for '(Clauses 3, 6.2, 7.2, 7.3, 7.4 and 7.4.1)'.

[Page 2, Table 2, clause reference, see also Amendment No. 1] — Substitute '(Clauses 3.2, 6.2, 6.3.2, 7.2, 7.3, 7.4 and 7.4.1)' for '(Clauses 3, 6.2, 7.2, 7.3, 7.4 and 7.4.1)'.

[Page 3, Table 3, clause reference, see also Amendment No. 1] — Substitute '(Clauses 3.2, 6.2, 6.3.2, 7.2, 7.3, 7.4 and 7.4.1)' for '(Clauses 3, 6.2, 7.2, 7.3, 7.4 and 7.4.1)'.

[Page 3, Table 3, col (3), heading] — Substitute 'Length' for 'Lengt'.

[Page 3, Table 4, clause reference, see also Amendment No. 1] — Substitute '(Clauses 3.2, 6.2, 6.3.2, 7.2, 7.3, 7.4 and 7.4.1)' for '(Clauses 3, 6.2, 7.2, 7.3, 7.4 and 7.4.1)'.

[Page 3, Table 5, clause reference, see also Amendment No. 1] — Substitute '(Clauses 3.2, 6.2, 6.3.2, 7.2, 7.3, 7.4 and 7.4.1)' for '(Clauses 3, 6.2, 7.2, 7.3, 7.4 and 7.4.1)'.

[Page 4, Table 6, clause reference, see also Amendment No. 1] — Substitute '(Clauses 3.2, 6.2, 6.3.2, 7.2, 7.3, 7.4 and 7.4.1)' for '(Clauses 3, 6.2, 7.2, 7.3, 7.4 and 7.4.1)'.

(Page 4, clause 7.2, last sentence) — Substitute the following for the existing:

'The minimum number of knuckles in the hinges of different sizes shall be as specified in Table 1 to Table 6. For any other dimensions, that is, combination of length, breadth, thickness of the flap and diameter of the pin, the minimum number of knuckles shall be declared by the manufacturer.'

(Page 4, clause 7.3) — Insert the following at the end:

'In case of welded hinges, the single pin shall be used and shall cover a minimum of 90 percent of the length of the hinge.'

(Page 5, clause 8) — Substitute the following for the existing:

## 8 CORROSION RESISTANCE AND FINISH

**8.1** Unless otherwise specified, hinges shall be either naturally finished bright or stove enameled black with smooth surface without chemical coating, and when tested for neutral salt spray test as per IS 5528 for following durations, shall pass the corrosion resistance requirements of respective grades:

- a) Grade 3: High resistance, up to 96 h; and
- b) Grade 4: Very high resistance, up to 240 h.

**8.2** After testing, the hinge sample(s) shall not show any corrosion on the visible surfaces.

**Amendment No. 2 to IS 12817 : 2020**

**8.3** In case of bearing hinges and welded hinges, the requirement of neutral salt spray test as per IS 5528 shall be of minimum grade 4 (*see 8.1*).

**8.4** Hinges in other finishes may also be supplied by manufacturer subject to conformity with the corrosion resistance requirements.’

(Page 5, clause 11) — Substitute the following for the existing:

‘**11.1** Hinges shall be packed in cardboard boxes or in any other packing which avoids damages to the product and injury to the purchaser.

**11.2** Each package shall be marked showing the following particulars:

- a) Manufacturer’s name or brand name or trade name;
- b) Construction (*see 3.1*) and type of hinges (*see 3.2*);
- c) Dimensions of hinges, that is, length, breadth and thickness of flap;
- d) Corrosion resistance grade (*see 8.1*);
- e) Grade and IS of material (both flap and pin); and
- f) Quantity of hinges.’