

AMENDMENT NO. 2 FEBRUARY 2025
TO
IS 13095 : 2020 BUTTERFLY VALVES FOR GENERAL PURPOSES
(First Revision)

(First cover, title) — Substitute the following for the existing:

‘सामान्य प्रयोजनार्थ बटरफ्लाई वाल्व — विशिष्टि
(पहला पुनरीक्षण)

Butterfly Valves for General Purposes — Specification
(First Revision)’.

(Page 1, title) — Substitute the following for the existing:

‘BUTTERFLY VALVES FOR GENERAL PURPOSES — SPECIFICATION
(First Revision)’.

[Page 2, clause 1.2 (see also Amendment No. 1)] — Substitute the following for the existing:

‘It covers valves of nominal pressure designations up to and including PN 4.0 with ends flanged or wafer type valves with bodies designed to be accommodated between pipe work flanges in accordance with appropriate tables of IS 6418, IS 9523 or IS 6392 in nominal sizes DN 40 to DN 2 000. It also covers flanges as per the pressure/temperature ratings given in IS 13159 (Part 1).’

[Page 2, clause 7.2 (see also Amendment No. 1)] — Delete.

(Page 3, clause 12) — Insert the following paras at the end:

‘Shaft design shall be anti-blowout proof design such that after removal of actuator, shaft shall remain in place withstanding the internal design pressure.

For better leak tightness, double or triple eccentric valve may be provided.’

[Page 4, Table 1 (see also Amendment No. 1)] — Delete ‘Class 125/250’ and ‘Class 300’ wherever they appear.

(Page 6, clause 16.6.4) — Insert the following new clause at the end:

‘16.7 When requested by the buyer, the manufacturer shall provide the valve position vs flow resistance curves.’

[Page 6, Table 3, table heading, col (3)] — Substitute ‘Seat Test and Disc Strength Test’ for ‘Seat Test When Applicable’.

[Page 7, clause 23.1.2(b)] — Substitute the following for the existing:

‘b) Power/voltage/frequency/No. of phases/air supply pressure/type of operator’.