

AMENDMENT NO. 4 FEBRUARY 2026
TO
IS 1884 : 1993 AUTOMOTIVE VEHICLES — ELECTRIC HORNS —
SPECIFICATION
(Third Revision)

(Page 1, clause 1) — Substitute the following for the existing:

‘1 SCOPE

This standard specifies the mechanical, electrical and acoustical requirements, methods of tests for 6 V, 12 V, 24 V and 48 V electric horns for use in motor vehicles including those intended for two and three wheelers.’

(Page 1, clause 2) — Substitute the following for the existing:

The standards given below contain provisions, which through reference in this text constitute provisions of the standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of these standards:

<i>IS No.</i>	<i>Title</i>
IS 269 : 2015	Ordinary portland cement — Specification
IS 10250 : 1982	Specification for severities for environmental tests for automotive electrical equipment
IS 15575	Electroacoustic — Sound level meters:
(Part 1) : 2016	Specifications
(Part 2): 2023	Pattern evaluation tests
IS/IEC 60068-2-1 : 2007	Environmental testing: Part 2 Tests, Section 1 Test A: Cold
IS/IEC 60068-2-2 : 2007	Environmental testing: Part 2 Tests, Section 2 Test B Dry heat
IS/IEC 60068-2-6 : 2007	Environmental testing: Part 2 Tests, Section 6 Test Fc: Vibration sinusoidal
IS/IEC 60068-2-17 : 2023	Environmental testing: Part 2 Tests, Section 17 Test Q: Sealing

(Page 2, clause 3.11) — Insert the following at the end:

‘3.12 Electro-Magnetic with Resonator Disc

A principle of operation by electro-magnetic force amplified by resonator disc.

3.13 Electro-Magnetic with Horn

A principle of operation by electro-magnetic force amplified by a horn.

3.14 Electronic

A principle of operation by electric or electro-magnetic force with amplifier and speaker or resonator.’

Amendment No. 4 to IS 1884 : 1993

[Page 5, clause **6.1**, (see also Amendment No. 1 and also Amendment No. 2)] — Substitute the following for the existing:

‘6.1 The values of current ratings for electric horns shall be as follows:

Sl No.	Rated Voltage	Maximum Rated Current Amperes			
		Type 1	Type 2		Type 3
			2A	2B	
(1)	(2)	(3)	(4)	(5)	(6)
i)	48 V d.c.	—	1.0	—	—
ii)	24 V d.c.	—	—	3	6
iii)	12 V d.c.	—	2.5	5	10
iv)	6 V d.c.	—	3	8	15
v)	6 V a.c. rms	3.5	—	—	—
vi)	12 V a.c. rms	3.5	—	—	—

[Page 5, clause **8.1.1(g)**] — Substitute ‘g) Endurance test (see **8.8**)’ for ‘g) Bndurance test (see **8.8**)’.

(Page 7, clause **8.5.1**) — Substitute the following for the existing:

‘8.5.1 The horn at ambient temperature shall operate satisfactorily over the following voltage.

Sl No.	Rated Voltage of Horn (V)	Performance Limits of Voltage	
		Maximum	Minimum
		(V)	(V)
(1)	(2)	(3)	(4)
i)	48	54.0	42.0
ii)	24	30.0	22.0
iii)	12	14.5	10.0
iv)	6	8.0	5.5

NOTE — The requirements specified in **8.5.1** shall be applicable for dc horns only. However, for ac horns the operating range shall be as agreed upon between the manufacturer and the purchaser.

(Page 7, clause **8.6.2**) — Substitute the following for the existing:

‘8.6.2 The supply voltage shall be (6.5 ± 0.1) V, (13 ± 0.1) V, (26 ± 0.1) V or (52 ± 0.1) V at the terminals of the source of electrical energy corresponding respectively to rated voltage of 6 V, 12 V, 24 V, 48V. The resistance of the connecting leads excluding any switch contact in circuit shall be not greater than 0.05, 0.10, 0.20, 0.40 ohm for rated voltage of 6 V, 12 V, 24 V and 48 V respectively.’

(Page 7, clause **8.6.5**, line 10) — Substitute ‘IS 15575 (1) and (2)’ for ‘IS 9779 : 1981’.

(Page 8, clause **8.8.2**) — Substitute the following for the existing:

Amendment No. 4 to IS 1884 : 1993

‘8.8.2 The voltage at the horn terminals shall be (6.5 ± 0.2) V, (13 ± 0.3) V, (26.0 ± 0.5) V and (52 ± 1) V for rated voltages 6 V, 12 V, 24 V, 48 V respectively. For Type 1 ac horns operation the power shall be supplied by the generator of the vehicles for which the horn is intended, or the test shall be carried out with a generator of similar design with speeds agreed mutually between the manufacturers and the purchasers. The resistance in the systems including the resistance at terminals and contacts shall be less than 0.05, 0.10, 0.20 and 0.4 ohms for rated voltages of 6 V, 12 V, 24 V and 48 V respectively.’

(Page 8, clause **8.9**, line 2) — Substitute ‘IS/IEC 60068-2- 6’ for ‘IS 9000 (Part 8) : 1981’.

(Page 9, clause **8.11**, para 1) — Substitute the following for the existing:

‘With a terminal voltage of (6.5 ± 0.1) V, (13 ± 0.2) V, (26 ± 0.4) V, (52 ± 1) V as appropriate, the horn shall be continuously operated for a period of five minutes and then allowed to cool to ambient temperature.’

(Page 9, clause **8.12**, line 5) — Substitute ‘IS 269’ for ‘IS 269 : 1989.’

(Page 10, clause **8.13**, line 2) — Substitute ‘IS 10250’ for ‘IS 10250 : 1982.’

(Page 11, clause **8.15.1**, line 2) — Substitute ‘IS/IEC 60068-2-17’ for ‘IS 9000 (Part 15/Sec 7) : 1982’.

(Page 11, clause **8.16.1**, line 6) — Substitute ‘IS/IEC 60068-2-2’ for ‘IS 9000 (Part 3/Sec 1) : 1977.’

(Page 11, clause **8.16.2**, line 6) — Substitute ‘IS/IEC 60068-2-1’ for ‘IS 9000 (Part 2/Sec 1 to 4) : 1977.’