

AMENDMENT NO. 1 SEPTEMBER 2017
TO
IS 1893 (PART 1) : 2016 CRITERIA FOR EARTHQUAKE
RESISTANT DESIGN OF STRUCTURES

PART 1 GENERAL PROVISIONS AND BUILDINGS

(Sixth Revision)

(Page 7, clause 6.3.2.2, line 3) — Substitute ‘Table 5(v)’ for ‘Table 5(e)’.

(Page 21, clause 7.4.2) — Insert the following new clause at the end:

‘7.5 Minimum Design Lateral Force

See 7.2.2.’

[Page 21, clause 7.6.2(b)] — Substitute the following for the existing formula of A_w :

$$A_w = \sum_{i=1}^{N_w} \left[A_{wi} \left\{ 0.2 + \left(\frac{L_{wi}}{h} \right) \right\}^2 \right]$$

(Page 27, clause 7.11.3, para 2, line 3) — Substitute ‘ $(R_1 \Delta_1 + R_2 \Delta_2) / 2$ ’ for ‘ $(R_1 \Delta_1 + R_2 \Delta_2)$ ’.

(Page 37, Annex E) — Substitute ‘Thiruvannamalai’ for ‘Tiruvannamalai’.

[Page 39, clause F-1, step 6(a)] — In para 4 under step 6(a), substitute ‘ $\alpha = 5$ ’ for ‘ $\alpha = 0.5$ ’