

AMENDMENT NO. 1 AUGUST 2005
TO
IS 10430 : 2000 CRITERIA FOR DESIGN OF
LINED CANALS AND GUIDANCE FOR SELECTION OF
TYPE OF LINING

(First Revision)

[Page 1, clause 3(r)] — Substitute the following for the existing:

‘r) Availability of suitable construction material within economic leads, such as:

- 1) Cement of requisite quality;
- 2) Building lime of requisite class;
- 3) Flyash for use as pozzolana;
- 4) Suitable clay for manufacture of calcined clay pozzolana;
- 5) Coarse and fine aggregates;
- 6) Soil of suitable quality for manufacture of burnt clay tiles/bricks;
- 7) Pulverized fuel ash-lime and/or clay flyash building bricks; and
- 8) Stones of required size and quality.’

[Page 3, clause 6(a)] — Substitute the following for the existing:

‘a) **Rigid Lining**

- 1) Stone-pitched lining;
- 2) Burnt clay tile or brick lining;
- 3) Burnt bricks or pulverized fuel ash-lime bricks or burnt clay flyash building bricks lining;
- 4) Precast cement concrete/stone slab lining;
- 5) Cement concrete tile lining;
- 6) In situ cement/lime concrete lining;
- 7) Stone masonry lining;
- 8) Soil cement/soil cement and flyash lining;
- 9) Shotcrete lining;
- 10) Ferrocement lining; and
- 11) Asphaltic cement concrete lining.

Amend No. 1 to IS 10430 : 2000

[Page 4, clause 6(b)(1)] — Substitute the following for the existing:

- 1) Geomembrane like High Density Polyethylene (HDPE), Polvinyl chloride (PVC), Low Density Polyethylene (LDPE) with cover comprising layer of bentonite with adequate earth/burnt clay tile brick or pulverized fuel ash-lime brick or burnt clay flyash building brick/precast cement concrete.'

(WRD 13)

Reprography Unit, BIS, New Delhi, India