

**AMENDMENT NO. 1 AUGUST 2021**

**TO**

**IS 10694 (PART 1) : 2009 AUTOMOTIVE VEHICLES —  
RIMS — GENERAL REQUIREMENTS**

**PART 1 NOMENCLATURE, DESIGNATION,  
MARKING AND MEASUREMENT**

*( Second Revision )*

*(Page 3, clause 3.1)* — Substitute the following for the existing clause:

**‘3.1 Present Designation**

The wheels/rims shall be designated by the following figures representing:

- a) Nominal rim width code;
- b) Rim profile;
- c) Nominal rim diameter code;
- d) A letter or letters signifying the tyre-side profile of the rim (usually the profile designation follows the nominal rim width; it may, however, precede or include the nominal rim width); and
- e) *Off the road* — The symbol ‘/’ followed by a figure or figures indicates the flange, height.

**Price Group 1**

*Example:*

| RIM MARKING            |                      | RIM CONTOUR   |         | NOMINAL<br>DIAMETER<br>CODE | SPECIAL<br>FEATURES                |
|------------------------|----------------------|---------------|---------|-----------------------------|------------------------------------|
|                        |                      | WIDTH<br>CODE | PROFILE |                             |                                    |
| PASSENGER CARS         |                      |               |         |                             |                                    |
| 4.5J × 15              | Or 15 × 4.5J         | 4.5           | J       | 15                          | —                                  |
| 4½ × 15                | Or 15 × 4½           | 4½            | J       | 15                          | —                                  |
| 4.5J × 15 H2           | Or 15 × 4.5J H2      | 4.5           | J       | 15                          | H2 Hump<br>Designation             |
| COMMERCIAL VEHICLES    |                      |               |         |                             |                                    |
| 5.0-20 (5.0 × 20)      | Or 20-5.0 (20 × 5.0) | 5             | —       | 20                          | —                                  |
| 22.5 × 7.50            | Or 7.50 × 22.5       | 7.50          | —       | 22.5                        | —                                  |
| 10.00 V-20             | Or 20-10.00 V        | 10            | V       | 20                          | —                                  |
| (10.00 V × 20)         | (20 × 10.00 V)       |               |         |                             |                                    |
| AGRICULTURAL TRACTORS  |                      |               |         |                             |                                    |
| W 15 L × 28            | Or 28 × W 15 L       | 15            | L       | 28                          | —                                  |
| MOTOR CYCLES           |                      |               |         |                             |                                    |
| 16 × 1.20              | Or 1.20 × 16         | 1.20          | —       | 16                          | —                                  |
| 18 × 2.15              | Or 2.15 × 18         | 2.15          | —       | 18                          | —                                  |
| 18 × MT 2.15 H2        | Or MT 2.15 × 18 H2   | 2.15          | MT      | 18                          | —                                  |
| SCOOTERS               |                      |               |         |                             |                                    |
| 8-2.10                 | Or 2.10-8            | 2.10          | —       | 8                           | —                                  |
| INDUSTRIAL/LIFT TRUCKS |                      |               |         |                             |                                    |
| 5.00F-10               | Or 10-5.00F          | 5.00          | F       | 10                          | —                                  |
| EARTHMOVING EQUIPMENT  |                      |               |         |                             |                                    |
| 8.00TG-24 SDC          | Or 24-8.00TG SDC     | 8.00          | TG      | 24                          | SEMI DROP<br>CENTRE<br>(SDC)       |
| 11.25-25/2.0           | Or 25-11.25/2.0      | 11.25         | —       | 25                          | CODE OF<br>FLANGE<br>HEIGHT (/2.0) |
| 25×14.00/1.3           | Or 14.00/1.3x25      | 14.00         | —       | 25                          | CODE OF<br>FLANGE<br>HEIGHT(/1.3)’ |

(Page 4, clause 4) — Substitute the following for the existing clause:

## **‘4 MARKING**

Wheels with integral or permanently affixed rims and rims separate or demountable shall be legibly marked with their size designation.

### **4.1 Marking of Rims**

Rims delivered without disc and being in compliance with the relevant Indian Standard shall be durably and legibly marked with the following:

- a) Size designation;
- b) Indication of the source of manufacture/manufacturer’s logo; and
- c) Rim bead seat contour type, if applicable (Rim bead seat contour type may be as given in ITTAC Manual or International standards).

**4.1.1** In case the markings are impressed or embossed, the letters shall not be smaller than 2 mm and impressed to a depth or embossed to a height of not less than 0.13 mm.

**4.1.2** In case other marking methods, for example, laser printing, pad printing, ink jet printing and stickers are used, such marking should be, legible, indelible, non-removable and durable.

**4.1.3** The location of the markings shall be as per the discretion of the manufacturer.

The rims may be marked on the outer-side (*see* Fig. 15 and Fig. 16) or inside (*see* Fig. 17).

### **4.2 Marking of Disc Wheel**

Disc wheels being in compliance with the relevant Indian Standard shall be durably and legibly marked with the following:

- a) Size designation;
- b) Indication of the source of manufacture/manufacturer’s logo;
- c) Date of manufacturing: year and month or year and quarter of the year (for example 21 03 indicates March 2021; 21 III indicates third quarter of 2021); and
- d) Half dual spacing or inset may also be marked.

**4.2.1** In case the markings are impressed or embossed, the marking shall be recessed and without sharp edges and letters shall not be smaller than 2 mm and impressed to a depth or embossed to a height not less than 0.13 mm.

**4.2.2** In case other marking methods, for example, laser printing, pad printing, ink jet printing and stickers are used, such marking should be legible, indelible, non-removable and durable.

**4.2.3** The location of the markings shall be at the discretion of the manufacturer. The rims may be marked on the outer-side (*see* Fig.18) or inside (*see* Fig.17).'