

AMENDMENT NO. 1 DECEMBER 1984
TO
IS : 2155 - 1982 SPECIFICATION FOR COLD
FORGED SOLID STEEL RIVETS FOR HOT CLOSING
(6 TO 16 mm DIAMETER)
(First Revision)

Corrigenda

(Page 2, Table 1, third column, *d Min*) — Substitute '7·85' for '5·85'.

(Page 2, Table 1, first column) — Substitute ' $r_k \approx$ ' for ' $r_k M \approx$ '.

Alteration

(Page 5, Table 4, first column) — Substitute

$$\begin{array}{ll} + \begin{smallmatrix} 0.5 \\ 0 \end{smallmatrix} \text{ for } l \leq 10 & + \begin{smallmatrix} 0.5 \\ 0 \end{smallmatrix} \text{ For } d \leq 10 \\ + \begin{smallmatrix} 1.0 \\ 0 \end{smallmatrix} \text{ for } 10 < l \leq 20 & \text{for } l \text{ Tol } + \begin{smallmatrix} 1.0 \\ 0 \end{smallmatrix} \text{ For } d > 10 \\ + \begin{smallmatrix} 1.5 \\ 0 \end{smallmatrix} \text{ for } l > 20 & \end{array}$$

(EDC 27)

Printed at New India Printing Press, Khurja, India