

AMENDMENT NO. 1 AUGUST 2024
TO
IS 2202 (PART 2) : 2022 WOODEN FLUSH DOOR SHUTTERS
(SOLID CORE TYPE) — SPECIFICATION
PART 2 PARTICLE BOARD, HIGH DENSITY FIBRE BOARD, MEDIUM DENSITY
FIBRE BOARD AND FIBRE HARDBOARD FACE PANELS
(Fourth Revision)

(Page 1, clause 1) — Insert the following at the end:

‘NOTES

1 This standard covers different construction of doors that is door having stiles and rails and door having particle/MDF board door blanks.

2 The requirements given in this standard are in addition or alternate to IS 2202 (Part 1).’

(Page 1, clause 6.2, line 5) — Substitute ‘BWP grade and MR grade of’ for ‘IS 710 and’.

(Page 2, Table 1) — Substitute the following for the existing:

‘Table 1 Designation of Wooden Flush Door Shutters, Solid Core Type with Particle Board, HDF, MDF and Fibre Hardboard Face Panels

[Clauses 4.2 and 13.1(c)]

Sl No.	Core	Type	Abbreviation
(1)	(2)	(3)	(4)
i)	Blockboard	Decorative with skins of any type of face panels mentioned in 6.3.3 .	B D P V
		Non-decorative with skins of particle board/MDF/HDF/fibre hardboard unveneered.	B N P
		Non-decorative with skins of particle board/HDF/MDF/fibre hardboard veneered with commercial veneers.	B N P V
ii)	Particle board	Decorative with skins of any type of face panels mentioned in 6.3.3 .	P D P V
		Non-decorative with skins of particle board/MDF/HDF/fibre hardboard unveneered.	P N P
		Non-decorative with skins of particle board/HDF/MDF/fibre hardboard veneered with commercial veneers.	P N P V
iii)	Medium density fibre board	Decorative with skins of any type of face panels mentioned in 6.3.3 .	M D P V
		Non-decorative with skins of particle board/MDF/HDF/fibre hardboard unveneered.	M N P
		Non-decorative with skins of particle board/HDF/MDF/fibre hardboard veneered with commercial veneers.	M N P V

Price Group 2

Amendment No. 1 to IS 2202 (Part 2) : 2022

(Page 4, clause 6.3.3) — Substitute the following for the existing:

‘For B D P V, P D P V and M D P V types of flush door shutters, face panel of particle board, MDF board, HDF board and fibre hardboard with decorative faces of PVC (poly vinyl chloride) foils or other type of foils (as agreed between the manufacturer and the purchaser) or ABS (acrylonitrile butadiene styrene) sheets, shall pass 1H of pencil hardness test as per Annex C to IS 17637. Face panel of prelaminated MDF or HDF shall meet the requirement of abrasion resistance Type IV of IS 14587. Face panels with any decorative laminates (as agreed between the manufacturer and the purchaser) and CPL (continuous pressed laminates) shall meet the requirements of type VLS of IS 2046.’

(Page 4, clause 6.4, line 2) — Substitute ‘infill board/core’ for ‘core’.

(Page 4, clause 6.5) — Substitute the following for the existing:

‘6.5 Infill Board

The swelling in thickness in 2 h of the particle board, MDF and HDF board for core when tested in accordance with IS 2380 (Part 17) shall not exceed 5 percent.’

(Page 4, clause 7.1, line 3) — Substitute ‘7.2, 7.3 and 7.4’ for ‘7.2 and 7.3’.

(Page 4, clause 7.2) — Substitute the following for the existing:

‘The face panel shall be formed by gluing by the hot or cold or high frequency press process on faces of the particle board or HDF board or MDF board or fibre hardboard with/without decorative laminates or PVC (poly vinyl chloride) or other type of foils (as agreed between the manufacturer and the purchaser) or CPL (continuous pressed laminates) or ABS (acrylonitrile butadiene styrene) sheet. The combined thickness of the face panels shall not be less than 3 mm.’

(Page 4, clause 7.3) — Insert the following at the end:

‘7.4 Door Blanks

Flush door shutters with particle board/MDF solid door blanks with or without additional face panels having edge banded or beaded edges type core shall be manufactured with core of particle board, MDF board or veneered particle board conforming to Grade 1 of IS 3087, Grade 1 of IS 12406, Grade 1 of IS 3097, respectively. The beading shall be of solid timber of any of the species, preferably from species mentioned in Annex B of IS 2202 (Part 1) or of PVC or ABS material. The beading shall be to the full thickness of the door. The thickness of the beading shall pass the screw withdrawal test. Faces of such doors shall have decorative faced panels meeting the properties of the faces as described in 6.3.3.’

(Page 4, clause 10.1) — Insert the following at the end:

‘For solid core door blank with edge banding or beaded edges, end immersion test and knife test shall not be applicable.’

(Page 6, Annex A) — Substitute ‘IS No.’ for ‘Sl No.’.

(Page 6, Annex A) — Insert the following at proper place in ascending order:

<i>‘IS No.</i>	<i>Title</i>
IS 2046 : 1995	Decorative thermosetting synthetic resin bonded laminated sheets specification (<i>second revision</i>)
IS 17637 : 2021	Performance requirements of surface finishes for furniture applications’.

Amendment No. 1 to IS 2202 (Part 2) : 2022

(Page 6, Annex A, IS 710) — Delete the following:

<i>'IS No.</i>	<i>Title</i>
IS 710 : 2010	Marine plywood — Specification (<i>second revision</i>)'.