

AMENDMENT NO. 2 JANUARY 1993

TO

IS 2223 : 1983 DIMENSIONS OF FLANGE MOUNTED AC INDUCTION MOTORS

(*Second Revision*)

(Page 13, Table 3) — Substitute the following for the existing table:

**TABLE 3 DIMENSIONS OF B-TYPE FLANGE FOR LARGE
FRAME NUMBER MOTORS***

(*Clauses 3.2, 3.3, and 4.1 and Fig. 1 and 4*)

FLANGE NUMBER	DIMENSIONS						
	M	N	P	S	T	LA	
				Drilled hole size	No.		
(1)	(2) mm	(3) mm	(4) mm	(5) mm	(6)	(7) mm	(8) mm
F 1 080 B	1 080	↑	1 150	28	8	↑	↑
F 1 180 B	1 180	↑	1 250	28	8 or 16	↑	↑
F 1 250 B †	1 250	↑	1 320	28	8	↑	↑
F 1 320 B	1 320	↑	1 400	28	8 or 16	↑	↑
F 1 400 B †	1 400	↑	1 480	28	8	↑	↑
F 1 500 B	1 500	see Note 1	1 600	28	12 or 24	see Note 1	see Note 2
F 1 700 B	1 700	↑	1 800	28	12 or 24	↑	↑
F 1 900 B	1 900	↑	2 000	35	12 or 24	↑	↑
F 2 000 B †	2 000	↑	2 120	38	12	↑	↑
F 2 120 B	2 120	↑	2 240	35	12 or 24	↑	↑
F 2 360 B	2 360	↑	2 500	35	16 or 32	↑	↑

NOTE 1 — The dimensions *N* and *T* in Table 3 are not specified because these are not normally required for large machines. Special requirements, if any, may be agreed between the manufacturer and the user.

NOTE 2 — The thickness of flange *LA* in Table 3, may be selected suitably depending on the type of construction.

*The details in this table are applicable to flange mounted motors of VI design with shaft downward.

†These flange numbers have been retained for the purpose of continuity and are not preferred.