

AMENDMENT NO. 1 DECEMBER 1977
TO
IS : 2243-1971 SPECIFICATION FOR DRILL CHUCKS
(First Revision)

Alteration

(*Page 4, clause 4.3.1, Table, values under l_1*) — Substitute the following for the existing values:

l_1
14°5 18°5
24°0 32°0
40°5 50°5

Addenda

(*Page 3, clause 4.1*) — Add the following sentence at the end of 'Note' given in the table:

' For related mounting details of chucks, *see* Appendix C. '

(*Page 4, clause 4.2*) — Add the following sentence at the end of 'Note' given in the table:

' For related mounting details of chucks, *see* Appendix C. '

(*Page 11, clause B-4*) — Add the following Appendix C after B-4.

TYPICAL CHUCK CAPACITIES BY TYPES AND RELATED MOUNTING DETAILS
(Note under Clauses 4.1 and 4.2)

Chuck Type	Capacity	Short Morse Taper Mounts*								Jacobs Taper Mounts†								Internal Threaded Mounts‡				External Threaded Mounts§	
		B 10	B 12	B 16	B 18	B 22	B 24	0	1	2	2	3	3	4	5	M 10 x 1	M 12 x 1/25	M 14 x 1/5	M 18 x 1/5	M 18 x 1	M 12 x 1/25		
Type I — General 5-jaw light duty chuck	0 — 4																						
	0 — 6-5	O						O								P				P			
	0 — 8	O						O								P				P			
	1-5 — 10		O					O								P				P			
Type H — General 5-jaw industrial or heavy duty chuck	1-5 — 15		O							O		O	O										
	3 — 16			O																			
	0 — 4																						
	0 — 6-5		P						P							P							
	0 — 8		P							P						P							
	1-5 — 10			P							P												
Type S — General 5-jaw industrial self operating (key less) chuck	2 — 15			P														P	O				
	3 — 16				P														O				
	5 — 20					O	P												P				
	0 — 4	P						P															
	0 — 6	P	P					P								P							
	0 — 8		P							P						O							
	0 — 10			P							P								O				
	0-8 — 15			P																P			
	3 — 16				P															P			

*See clause 4.3.1.
†See clause 4.3.2.
‡See clause 4.3.3.
§See clause 4.3.4.

Note — P : Preferred mount.

O : Non-preferred mount. Other mounts can be obtained by special arrangements.

(SDG 11)