



AMENDMENT NO. 1 JULY 1983

TO

**IS : 2325-1981 SPECIFICATION FOR
IGNITION COILS FOR BATTERY-COIL IGNITION
SYSTEMS FOR AUTOMOBILES**

(*First Revision*)

Alteration

(*Page 9, clause 7.0.4, Note*) — Delete.

Addenda

(*Page 9, clause 7.0.4*) — Add the following new clause after **7.0.4**:

'**7.0.4.1** *Sampling plan* — A recommendatory sampling plan and criteria for acceptance of lot is given in Appendix C. '

[*Page 19, clause B-1.7(e)*] — Add the following new Appendix after **B-1.7(e)**:

' APPENDIX C

(*Clause 7.0.4.1*)

SCALE OF SAMPLING AND CRITERIA FOR CONFORMITY

C-1. LOT

C-1.1 In any consignment, the ignition coils of the same type and size manufactured from the same material in the same factory under similar conditions of production shall be grouped together to constitute a lot.

C-2. SCALE OF SAMPLING

C-2.1 For judging the conformity of the lot to the requirements of the specification, tests shall be done for each lot separately. For this purpose, the number of ignition coils to be selected at random from a lot shall be in accordance with col 1 and 2 of Table 1.

TABLE 1 SCALE OF SAMPLING AND ACCEPTANCE NUMBER

(Clauses C-2.1, C-3.1 and C-3.2)

LOT SIZE	FOR VISUAL AND DIMENSIONAL REQUIREMENTS		FOR PERFORMANCE AND HERMETIC SEALING TESTS	
	Sample Size	Acceptance Number	Sample Size	Acceptance Number
(1)	(2)	(3)	(4)	(5)
Up to 150	13	0	3	0
151 „ 300	20	1	5	0
301 „ 500	32	2	8	0
501 „ 1 000	50	3	13	0
1 001 and above	80	5	20	1

C-2.1.1 These coils shall be selected from the lot at random. In order to ensure the randomness of selection, procedures given in IS : 4905-1968* may be followed.

C-3. NUMBER OF TESTS AND CRITERIA FOR CONFORMITY

C-3.1 Each of the ignition coils selected in the sample in accordance with col 1 and 2 of Table 1 shall be subjected to visual examination and dimensional requirements. An ignition coil failing to satisfy either of the requirements shall be termed as 'defective'. The lot shall be considered as conforming to these requirements if the number of defectives found in the sample is less than or equal to the corresponding acceptance number (see col 3 of Table 1), otherwise the lot shall be considered as not conforming to these requirements.

C-3.2 The lot which has been found as conforming to the above requirements shall then be subjected to performance test and hermetic sealing test. For this purpose, a sample size and the corresponding acceptance numbers are given in col 4 and 5 of Table 1.

C-3.3 The lot shall be considered as conforming to the requirements of acceptance tests if **C-3.1** and **C-3.2** are satisfied, otherwise the lot shall be rejected.'

*Methods for random sampling.