

AMENDMENT NO. 1 FEBRUARY 2022

TO

IS 15140 : 2018 AUTOMOTIVE VEHICLES — SAFETY BELT AND RESTRAINT SYSTEMS — SPECIFICATION

(*First Revision*)

(Page 7, clause **4.2.5.3**, line 6) — Substitute ‘3 g’ for ‘2 g’.

(Page 9, clause **4.4.2.9(b)**, line 11) — Substitute ‘Fig. 26’ for ‘Fig. 25’.

(Page 20, clause **5.5.2.8**, line 2) — Substitute ‘Fig. 16’ for ‘Fig. 15’.

(Page 20, clause **5.5.2.10(b)(2)**, line 3) — Substitute ‘Fig. 20’ for ‘Fig. 19’.

(Page 20, clause **5.5.2.10(b)(2)**, line-13) — Substitute ‘total velocity change ΔV shall be $51 \pm^2_0$ km/h.’ for ‘total velocity change ΔV shall be km/h’.

(Page 20, clause **5.5.2.10(b)(2)**, line-13) — Delete ‘ 51^{+2}_{-0} ’

(Page 20, clause **5.5.2.11**, line-9) — Substitute ‘The distance to achieve the first 50^{+1}_{-0} km/h’ for ‘The distance to achieve the first km/h’.

(Page 21, clause **5.6**, line 6) — Substitute ‘Fig. 16’ for ‘Fig. 15’.

(Page 25, Annex-D, clause **D-3.2**, line-4) — Substitute ‘Fig. 16’ for ‘Fig. 15’.

(Page 26, Annex-D, clause **D-4.4.3**) — Substitute ‘Minimum Elongation: $A_o \geq 400$ percent’ for ‘Minimum Elongation: A_o 400 percent.

(Page 26, Annex D, *clause D-4.4.4*) — Substitute the following for the existing:

‘D-4.4.4 Modulus

- a) At 100 percent elongation $\geq 108 \text{ daN/cm}^2$
- b) At 300 percent elongation $\geq 235 \text{ daN/cm}^2$

(Page 26, Annex D, *clause D-4.4.6*) — Substitute ‘Compression set (Method B): 22 h at 70°C $\leq$ 45 percent’ for ‘Compression set: 22 h at 70°C (Method B) 45 percent’.

(Page 27, Annex D, *clause D-5.1.1(a)*, line-5) — Substitute ‘Manikin seated in a position shown in Fig. 16’ for ‘Fig. 26 Manikin in sitting position, showing’.

(Page 27, Annex D, *clause D-4.5*, line 2) — Substitute ‘D-4 above’ for ‘4.6 below’.

(Page 28, Annex D, *clause D-5.1.2.6*, line 2) — Substitute ‘tensioner’ for ‘pensioner’.

(Page 31, Annex D, *clause D-5.4.2(d)*, line 1) — Substitute ‘tensioner (28)’ for ‘tensioner’.