

AMENDMENT NO. 1 OCTOBER 2008
TO
IS 10942 : 2000 FERRULE — SPECIFICATION

(First Revision)

[Page 2, clause **3.2.1**, Table for Type A and Type B *Ferrule*] — Substitute the table given on page 2 of this Amendment for the existing:

All dimensions in millimeters.

Type	Ferrule Code	Length Before Pressing, Min, <i>L</i>	Length After Pressing, Min	Thickness, Min <i>T</i>	Suitable for Actual Wire Rope Size	
					Lower Limit	Upper Limit
1	2	3	4	5	6	7
Type A	3	11	17	1.61	2.90	3.15
	4.5	18	22	1.70	4.40	4.75
	6	19	23	2.10	5.85	6.30
	8	27	34	3.00	7.85	8.40
	9	30	34	3.50	8.80	9.45
	10	32	35	3.75	9.80	10.50
	11	36	43	5.25	10.75	11.55
Type B	13	45	53	4.20	11.75	13.65
	15	46	58	4.50	13.76	15.75
	17	50	60	5.20	15.76	17.85
	19	56	62	5.90	17.86	19.99
	21	62	70	6.20	20.00	21.99
	23	78	96	7.55	22.00	23.99
	25	83	100	8.00	24.00	25.99
	27	92	108	8.85	26.00	27.99
	29	98	114	9.85	28.00	29.99
	31	101	115	10.00	30.00	31.99
	33	105	118	11.07	32.00	33.99
	35	108	136	11.20	34.00	35.99
	37	115	144	11.80	36.00	37.99
	39	121	152	12.50	38.00	39.99
	41	127	160	13.10	40.00	41.99
	43	134	168	13.80	42.00	43.99
	45	141	177	14.60	44.00	46.99
	48	151	189	15.50	47.00	50.00
	51	160	201	16.50	50.00	52.99
	54	169	213	17.40	53.00	55.99
	57	178	224	18.40	56.00	58.99
	60	188	236	19.40	59.00	61.99
	63	197	248	20.30	62.00	64.99
	66	206	259	21.30	65.00	67.99
	69	216	271	22.20	68.00	70.99

(MED 10)