

AMENDMENT NO. 1 MARCH 1989

TO

IS : 11089 - 1984 CODE OF PRACTICE FOR DESIGN AND CONSTRUCTION OF RING FOUNDATION

(Page 3, clause 0.2, line 3) — Add the word ' circular ' after the word ' continuous '.

(Page 5, clause 4.3, line 2) — Substitute ' IS : 1904-1986† ' for ' IS : 1904-1978† '.

(Page 5, foot-note marked with ' † ' mark) — Substitute the following for the existing foot-note:

' †Code of practice for design and construction of foundation in soils: General requirements (third revision). '

(Page 10, clause 5.2.1, caption of formulae) — Substitute ' Uniform Pressure ' for the word ' Radial '.

(Page 10, last line) — Substitute the following for the existing line:

$$- 4B^3 \left\{ \log_e R + \frac{3}{4} \left(-\frac{1}{3} + \frac{1}{B^2} + \frac{1}{R^2} \right) + \left(\frac{1+R^2}{1-B^2} \right) \frac{B^2}{R^2} \log_e B \right\}$$

(Page 11, lines 1 and 2 of the formulae) — Substitute the following for the existing lines:

$$M_r = \frac{\rho_o a^2}{16} \left[4 \left(1 - \frac{B^2}{R^2} \right) \left(\frac{1}{2} \log_e C - \frac{C^2}{2} \right) + 3R^2 \right. \\ \left. - 4B^3 \left\{ \log_e R + \frac{3}{4} \left(1 + \frac{1}{B^2} - \frac{1}{R^2} \right) - \left(\frac{1-R^2}{1-B^2} \right) \frac{B^2}{R^2} \log_e B \right\} \right]$$

(Page 11, line 6) — Substitute ' Varying Pressure ' for the word ' Tangential '.

(Page 13, clause 6.1, line 4) — Substitute ' IS : 1893-1984† ' for ' 1893-1975† '.

(Page 13, foot-note marked with ' † ' mark) — Substitute the following for the existing foot-note:

' †Criteria for earthquake resistant design of structures (fourth revision). '