

AMENDMENT NO. 1 OCTOBER 2025
TO
IS 11188 (PART 1) : 2021 VAULT (STRONG ROOM) DOORS
PART 1 SPECIFICATION
(Third Revision)

(Page 1, clause 8.1.1) — Substitute the following for the existing:

‘8.1.1 Ventilating Grill Gate (Optional)

Ventilating grill gate, if provided, shall be made of mild steel angles, plates or channels with mild steel rods welded in a rigid frame. The mild steel rods shall be welded on the underside of the frame with the holes drilled in the upper and lower horizontal member of the shutter frame after passing through the flats or channels at the centre of the shutter frame. The grill gate shall be hinged in strong room doors frame such that it opens inside or outside, either from left to right or from right to left as required by the user. Alternatively, the grill gate also can be of sliding type.’

(Page 5, clause 8.4) — Substitute the following for the existing:

‘8.4 Locks

In accordance with SI No. (xiii) of Table 1, either key locks or combination locks shall be used. The lock shall be fixed with at least four bolts of 8 mm diameter such that any pressure applied on the bolts either directly or through the handle of the door, is not transmitted to the fixing screw of the lock or locks.’

(Page 5, clause 8.4.1) — Substitute the following for the existing:

‘8.4.1 Key Locks

Key locks when used in accordance with SI No. (xiii) of Table 1, shall be in compliance with type A of IS 17566. Grade of the locks shall be A3 or higher (A3 to A14). The keys shall be double bitted for Classes A, AA and AAA doors and single bitted type for Classes C and B with detachable key bit where necessary.’

(Page 5, clause 8.4.2) — Substitute the following for the existing:

‘8.4.2 Mechanical Combination Locks

Mechanical combination locks when used in accordance with SI No. (xiii) of Table 1, shall be in compliance with class I (or class II or class III) of IS 16723.’

(Page 5, clause 8.4.3) — Substitute the following for the existing:

‘8.4.3 Any Other Lock

Electronic combination lock or any other type of lock may be provided in addition to the number of locks given in SI No. (xiii) of Table 1.’

(Page 5, clause 9.3) — Substitute the following for the existing:

‘9.3 Foot Bridge (Optional)

In case of doors of Class A, AA and AAA, a hinged chequered steel footbridge can be provided to facilitate the passage of trolleys, etc. into the vault. The footbridge shall be folded into the vestibule before the door is closed. It shall not be applicable to emergency door.’

(MED 24)

Price Group 1
Publication, BIS, New Delhi