

AMENDMENT NO. 1 APRIL 2026

TO

**IS 11241 : 2024 PORTABLE LIQUEFIED PETROLEUM GAS APPLIANCES
OPERATING AT VAPOUR PRESSURE — SPECIFICATION**

(First Revision)

(Page 30, clause 6.30.1, Paragraph 7) — Substitute the following for the existing:

‘The efficiency is calculated from the equation:

$$\eta = M_e C_p \frac{(t_2 - t_1)}{M \cdot H_s} \times 100$$

where

η = is the efficiency in percentage; and

M_e = is the water equivalent of the vessel filled as indicated in the table above;

The mass M_e is made up as follows:

$$M_e = M' + 0.213 m$$

where

M' = is the mass of water put into the vessel; and

m = is the mass of aluminium corresponding to the test vessel covered by its lid (the mass m to be taken into account shall be the mass measured).

All masses are expressed in kilograms:

t_1 = is the water temperature in °C at the start of the test;

t_2 = is the water temperature in °C after extinction;

M = is the mass of gas burnt in kg (under the reference conditions of the gross calorific value);

H_s is the gross calorific value of gas in MJ/kg.

$C_p = 4.186 \times 10^{-3}$ MJ/kg/°C.

The requirements defined in **5.30.1.1** shall be met.’

(MED 23)

Price Group 1
Publication, BIS, New Delhi