

AMENDMENT NO. 1 JUNE 2026
TO
IS 206 : 2010 TEE AND STRAP HINGES — SPECIFICATION
(Fifth Revision)

(Page 1, clause 1, line 1) — Delete ‘mild’.

(Page 1, clause 2) — Substitute the following for the existing:

‘2 REFERENCES

The standards given below contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent edition of these standards:

<i>IS No.</i>	<i>Title</i>
IS 280 : 2006	Mild steel wire for general engineering purposes (<i>fourth revision</i>)
IS 513 (Part 1) : 2016	Cold reduced carbon steel sheet and strip: Part 1 Cold forming and drawing purpose (<i>sixth revision</i>)
IS 1079 : 2017	Hot rolled carbon steel sheet, plate and strip — Specification (<i>seventh revision</i>)
IS 5528 : 2024/ ISO 9227 : 2022	Corrosion tests in artificial atmospheres — Salt spray tests (<i>second revision</i>)
IS 5986 : 2017	Hot rolled steel sheet, plate and strip for forming and flanging purposes — Specification (<i>fourth revision</i>)
IS 6528 : 2024	Stainless steel wire — Specification (<i>second revision</i>)
IS 6760 : 1972	Specification for slotted countersunk head wood screws
IS 6911 : 2026	Stainless steel plate, sheet and strip — Specification (<i>third revision</i>)
IS 7887 : 1992	Mild steel wire rod for general engineering purposes — Specification (<i>first revision</i>)
IS 10748 : 2025	Hot-rolled steel plates, sheets and strips for welded tubes and pipes — Specification (<i>third revision</i>)
IS 11513 : 2017	Hot rolled carbon steel strip for cold rolling purposes — Specification (<i>second revision</i>)’

(Page 1, clause 4) — Substitute the following for the existing:

‘4 MATERIAL

4.1 Material used for manufacture of tee and strap hinges shall comply with the requirements given in Indian Standards mentioned in col (3) of Table 1.

4.2 Other steel materials may also be used as agreed between the manufacturer and the purchaser. However, the Indian Standard and grade of that material shall be declared by the manufacturer.

Amendment No. 1 to IS 206 : 2010

Table 1 Requirements of Materials for Tee and Strap Hinges

(Clause 4.1)

SI No.	Material	References to IS
(1)	(2)	(3)
i)	Mild steel sheet	IS 1079, IS 513 (Part 1), IS 10748, IS 11513 and IS 5986
ii)	Stainless steel sheet	IS 6911
iii)	Mild steel wire	IS 280 and IS 7887
iv)	Stainless steel wire	IS 6528'

(Page 1, clause 5.1.1) — Insert the following at the end:

5.2 In each designation (*see 3*), any other dimensions, that is, combination of length, breadth, thickness of flap and diameter of pin, may also be manufactured as agreed between the manufacturer and the purchaser. However, the thickness of the flap and the diameter of the pin shall not be less than the nearest higher size of the hinge in same designation. Also in such cases, the size designation of countersunk head wood screws, number of holes in strap and tee, *G*, *R*, *X* and *Y* shall be declared by the manufacturer.

5.2.1 The tolerance on any other dimensions shall be as follows:

- Length (*A*): ± 0.5 mm;
- Breadth (*B* and *F*): ± 1 mm and ± 2 mm respectively;
- Length (*C*) (for tee hinges only): ± 1.5 mm; and
- Width of knuckle (*G*, in case of tee hinges and *E*, in case of strap hinges): ± 1 mm.

5.2.2 For thickness of flap, where specified as '*E Min*' in case of tee hinges and '*C Min*' in case of strap hinges, from Table 2 to Table 12, a manufacturing tolerance of -0.05 mm shall be allowed on the finished product with respect to the specified value.

NOTES

1 For example, in Table 2, where the thickness of flap (*E Min*) is specified as 1.60 mm for size 75, the minimum acceptable thickness on the finished product shall be 1.55 mm.

2 For example, in Table 9, where the thickness of flap (*C Min*) is specified as 2.24 mm for size 400, the minimum acceptable thickness on the finished product shall be 2.19 mm.'

(Page 1, clause 7) — Substitute the following for the existing:

7 CORROSION RESISTANCE AND FINISH

7.1 Unless otherwise specified, hinges shall be either bright finished or stove enameled black and when tested for neutral salt spray test as per IS 5528 for following durations, shall pass the corrosion resistance requirements of respective grades:

- Grade 0 — No requirement;
- Grade 1 — Mild resistance, up to 24 h;
- Grade 2 — Moderate resistance, up to 48 h;
- Grade 3 — High resistance, up to 96 h; and
- Grade 4 — Very high resistance, up to 240 h.

7.2 After testing, the hinge sample(s) shall not show any corrosion on the visible surfaces.

7.3 Hinges of other finishes may also be supplied by manufacturer subject to conformity with the corrosion resistance requirements.'

(Page 1, clause 8) — Substitute the following for the existing:

‘8 PACKING

8.1 Hinges shall be packed in cardboard boxes or in any other packing which avoids damages to the product and injury to the purchaser.

8.2 Each package shall be marked showing the following particulars:

- a) Manufacturer’s name or brand name or trade name;
- b) Construction (tee hinge or strap hinge) and designation of hinges;
- c) Dimensions of hinges, that is, length, breadth and thickness of flap;
- d) Corrosion resistance grade (*see 7.1*);
- e) Grade and IS of material (both flap and pin); and
- f) Quantity of hinges.’

[Page 3, Table 2, clause reference] — Substitute ‘(Clauses 5.1, 5.2.2 and 6)’ for ‘(Clauses 5.1 and 6)’.

[Page 3, Table 2, col (6), heading] — Substitute ‘*D Min*’ for ‘*D*’.

[Page 3, Table 2, col (7), heading] — Substitute ‘*E Min*’ for ‘*E*’.

[Page 3, Table 2, Sl No. (i) to (viii), col (6)] — Delete ‘ ± 0.05 ’.

[Page 3, Table 2, Sl No. (ix), col (6)] — Delete ‘ ± 0.06 ’.

[Page 3, Table 2, Sl No. (i) to (ix), col (7)] — Delete ‘ ± 0.10 ’.

[Page 3, Table 3, clause reference] — Substitute ‘(Clauses 5.1, 5.2.2 and 6)’ for ‘(Clauses 5.1 and 6)’.

[Page 3, Table 3, col (6), heading] — Substitute ‘*D Min*’ for ‘*D*’.

[Page 3, Table 3, col (7), heading] — Substitute ‘*E Min*’ for ‘*E*’.

[Page 3, Table 3, Sl No. (i) to (v), col (6)] — Delete ‘ ± 0.05 ’.

[Page 3, Table 3, Sl No. (i) to (v), col (7)] — Delete ‘ ± 0.10 ’.

[Page 4, Table 4, clause reference] — Substitute ‘(Clauses 5.1, 5.2.2 and 6)’ for ‘(Clauses 5.1 and 6)’.

[Page 4, Table 4, col (6), heading] — Substitute ‘*D Min*’ for ‘*D*’.

[Page 4, Table 4, col (7), heading] — Substitute ‘*E Min*’ for ‘*E*’.

[Page 4, Table 4, Sl No. (i) to (v), col (6)] — Delete ‘ ± 0.05 ’.

[Page 4, Table 4, Sl No. (vi) to (xi), col (6)] — Delete ‘ ± 0.06 ’.

[Page 4, Table 4, Sl No. (i) to (xi), col (7)] — Delete ‘ ± 0.10 ’.

[Page 4, Table 5, clause reference] — Substitute ‘(Clauses 5.1, 5.2.2 and 6)’ for ‘(Clauses 5.1 and 6)’.

Amendment No. 1 to IS 206 : 2010

[Page 4, Table 5, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 4, Table 5, col (7), heading] — Substitute '*E Min*' for '*E*'.

[Page 4, Table 5, Sl No. (i) to (iii), col (6)] — Delete ' ± 0.05 '.

[Page 4, Table 5, Sl No. (iv) to (xii), col (6)] — Delete ' ± 0.06 '.

[Page 4, Table 5, Sl No. (i) to (xii), col (7)] — Delete ' ± 0.10 '.

[Page 5, Table 6, clause reference] — Substitute '(Clauses 5.1, 5.2.2 and 6)' for '(Clauses 5.1 and 6)'.

[Page 5, Table 6, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 5, Table 6, col (7), heading] — Substitute '*E Min*' for '*E*'.

[Page 5, Table 6, Sl No. (i) to (ix), col (6)] — Delete ' ± 0.06 '.

[Page 5, Table 6, Sl No. (i) to (ix), col (7)] — Delete ' ± 0.10 '.

[Page 5, Table 7, clause reference] — Substitute '(Clauses 5.1, 5.2.2 and 6)' for '(Clauses 5.1 and 6)'.

[Page 5, Table 7, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 5, Table 7, col (7), heading] — Substitute '*E Min*' for '*E*'.

[Page 5, Table 7, Sl No. (i) to (vi), col (6)] — Delete ' ± 0.06 '.

[Page 5, Table 7, Sl No. (i) to (vi), col (7)] — Delete ' ± 0.10 '.

[Page 6, Table 8, clause reference] — Substitute '(Clauses 5.1, 5.2.2 and 6)' for '(Clauses 5.1 and 6)'.

[Page 6, Table 8, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 6, Table 8, col (7), heading] — Substitute '*E Min*' for '*E*'.

[Page 6, Table 8, Sl No. (i) to (iii), col (6)] — Delete ' ± 0.08 '.

[Page 6, Table 8, Sl No. (i) to (iii), col (7)] — Delete ' ± 0.10 '.

[Page 6, Table 9, clause reference] — Substitute '(Clauses 5.1, 5.2.2 and 6)' for '(Clauses 5.1 and 6)'.

[Page 6, Table 9, col (5), heading] — Substitute '*C Min*' for '*C*'.

[Page 6, Table 9, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 6, Table 9, Sl No. (i) to (ix), col (5)] — Delete ' ± 0.10 '.

[Page 6, Table 9, Sl No. (i) to (ix), col (6)] — Delete ' ± 0.05 '.

[Page 7, Table 10, clause reference] — Substitute '(Clauses 5.1, 5.2.2 and 6)' for '(Clauses 5.1 and 6)'.

[Page 7, Table 10, col (5), heading] — Substitute '*C Min*' for '*C*'.

[Page 7, Table 10, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 7, Table 10, Sl No. (i) to (xi), col (5)] — Delete ' ± 0.10 '.

[Page 7, Table 10, Sl No. (i) to (xi), col (6)] — Delete ' ± 0.05 '.

[Page 7, Table 11, clause reference] — Substitute '(Clauses 5.1, 5.2.2 and 6)' for '(Clauses 5.1 and 6)'.

[Page 7, Table 11, col (5), heading] — Substitute '*C Min*' for '*C*'.

[Page 7, Table 11, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 7, Table 11, Sl No. (i) to (v), col (5)] — Delete ' ± 0.10 '.

[Page 7, Table 11, Sl No. (i), col (6)] — Delete ' ± 0.05 '.

[Page 7, Table 11, Sl No. (ii) to (v), col (6)] — Delete ' ± 0.06 '.

[Page 8, Table 12, clause reference] — Substitute '(Clauses 5.1, 5.2.2 and 6)' for '(Clauses 5.1 and 6)'.

[Page 8, Table 12, col (5), heading] — Substitute '*C Min*' for '*C*'.

[Page 8, Table 12, col (6), heading] — Substitute '*D Min*' for '*D*'.

[Page 8, Table 12, Sl No. (i) to (ix), col (5)] — Delete ' ± 0.10 '.

[Page 8, Table 12, Sl No. (i) to (ix), col (6)] — Delete ' ± 0.06 '.