

AMENDMENT NO. 1 MARCH 2024

TO

**IS 458 : 2021 PRECAST CONCRETE PIPES (WITH AND WITHOUT REINFORCEMENT) —
SPECIFICATION**

(Fifth Revision)

(Page 11, Table 5) — Add following at the end of the table before note:

(1)	(2)	(3)	(4)	(5)	(6)	(7)
2 600	240	12 + 2	14.88	146.61	124.54	186.81

(Page 14, Table 8) — Add following at the end of the table before note:

(1)	(2)	(3)	(4)	(5)	(6)	(7)
2 200	210	12 + 2	14.88	125.28	142.20	213.30
2 400	225	12 + 2	14.88	154.94	155.00	232.50
2 600	240	12 + 2	14.88	181.25	166.70	250.00

[Page 20, Table 13, entry of col (15) against 700] — Substitute '52' for '47'.

(Page 20, Table 13, Note 1) — Substitute the following for the existing:

‘The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2.**’

[Page 21, Table 13A, entry of col (15) against 700] — Substitute '52' for '47'.

(Page 22, Table 13A, Note 2) — Substitute the following for the existing:

‘The procedure for the inspection is given in **10.2.2.**’

(Page 22, Table 13A, Note 1) — Substitute the following for the existing:

‘The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2.**’

(Page 24, Table 14, Note 1) — Substitute the following for the existing:

‘The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2.**’

(Page 25, Table 15A, Note 5) — Substitute the following for the existing:

‘Tolerance on $D_3 \pm 4$, $L_2 \pm 2$.’

(Page 26, Table 15B, heading) — Substitute the heading of the table with the following:

**‘Table 15B Spigot and Socket Dimensions for NP-3 Reinforced and Unreinforced + NP-4 Reinforced
Pipes Made by Vibration Casting Process from 300 mm to 1 800 mm Diameter’.**

Price Group 1

Amendment No. 1 to IS 458 : 2021

[Page 26, Table 15B, col (8) sub-heading] — Substitute ' d_s ' for ' d_m '.

(Page 27, Table 15B, Note 5) — Delete.

(Page 28, Table 15C) — Add following at the end of the table before note:

d_i	G	R	T	l_t	L_b	d_s	D_m	L_m	l_s	S	D_o	d_{so}	d_{sp}
2 600 ± 12	28	2 450	240	130 ± 4	130 ± 3	2 811	2 845	70	52	17 ± 1.5	3 080 ± 6	117.5	105.5

(Page 28, Table 15C, Note 4) — Substitute the following for the existing:

' l_t , L_b , d_s , D_m , L_m , l_s , d_{so} and d_{sp} are nominal dimensions.'

(Page 32, Table 17, Note 1) — Substitute the following for the existing:

'The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2**.'

(Page 34, Table 18, Note 1) — Substitute the following for the existing:

'The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2**.'

(Page 35, Table 18A) — Substitute the heading of the table with the following:

'Table 18A Spigot and Socket Dimensions of P2 Class Pipes (Rubber Ring Roll on Joint) Pipes Made by Vibrated Casting Process'.

(Page 36, Table 18A, Note 1) — Substitute the following for the existing:

'The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2**.'

(Page 38, Table 19, Note 1) — Substitute the following for the existing:

'The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2**.'

(Page 39, Table 19A, Note 1) — Substitute the following for the existing:

'The outside diameter of spigot and inside diameter of socket shall be checked as per **10.2.2**.'

(Page 44, clause **8.2**, Table, Note) — Add the following at the end:

'The above tolerances shall be applicable only where the tolerances are not mentioned.'

(Page 45, clause **10.2.2**) — Substitute the following for the existing:

'The diameter of spigot and socket shall be checked at four locations, equally spaced throughout the circumference of pipe. The dimensions which are mentioned as nominal in this Indian standard, should be for reporting purpose only. All the figures given with the tables are typical in nature and it is for illustration purpose only.'

(Page 45, Table 23, Note) — Delete.