

**AMENDMENT NO. 1 JUNE 2024**

**TO**

**IS 550 (PART 1) : 2022 SAFES**

**PART 1 SPECIFICATION**

*( Sixth Revision )*

*(Page 1, clause 1)* — Substitute the following for the existing:

‘This standard (Part 1) specifies the dimensions, general requirements and performance criteria for high security burglary resistant safes with double wall construction on all six sides, (hereafter called as safes).’

*(Page 2, Table 1)* — Substitute the following for the existing:

**Table 1 Classification of Safes**

*(Clauses 4, 8.3, 12.2 and 12.4)*

| Sl No. | Class | Classification Code         | Remarks                                                                                                                                                               |
|--------|-------|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (1)    | (2)   | (3)                         | (4)                                                                                                                                                                   |
| i)     | E     | TL 10 × 6 – FR30            | Safe having tool resisting capacity on all six sides for 10 min each and with fire resisting capacity of 30 min                                                       |
| ii)    | D     | Deposit safe (DEP 15 – D)   | Safe with door having tool resisting capacity of 15 min and resistance to trapping/fishing deposited envelops or bags for 15 min                                      |
| iii)   | C     | TL 30 D × TL 10 × 5 – FR 30 | Safe with door having tool resisting capacity of 30 min and other five sides having tool resisting capacity of 10 min each and with fire resisting capacity of 30 min |
| iv)    | CC    | TL 15 × 6 – FR 30           | Safe having tool resisting capacity on all six sides for 15 min each and with fire resisting capacity of 30 min                                                       |
| v)     | CCC   | TL 30 × 6 – FR 30           | Safe having tool resisting capacity on all six sides for 30 min each and with fire resisting capacity of 30 min                                                       |
| vi)    | BB    | TRTL – 15 × 6               | Safe having torch and tool resisting capacity on all six sides for 15 min each                                                                                        |
| vii)   | A     | TRTL – 30 × 6               | Safe having torch and tool resisting capacity on all six sides for 30 min each                                                                                        |
| viii)  | A+    | TRTL – 45 × 6               | Safe having torch and tool resisting capacity on all six sides for 45 min each                                                                                        |
| ix)    | AA    | TRTL – 60 × 6               | Safe having torch and tool resisting capacity on all six sides for 60 min each                                                                                        |
| x)     | AAA   | TRTL – 90 × 6               | Safe having torch and tool resisting capacity on all six sides for 90 min each                                                                                        |
| xi)    | X     | TXTL – 60 × 6               | Safe having torch and tool resisting capacity on all six sides for 60 min each and explosive resistance when tested in line with IS 550 (Part 2)                      |

NOTE — Time specified is minimum.

**Price Group 1**

(Page 2, clause **8.6.1**, line 3) — Substitute ‘Grade of the locks shall be minimum A4 or higher.’ for  
‘Grade of the locks shall be A4 or A6 or A8 or A12 or A13 or A14.’

(MED 24)

---

Publication, BIS, New Delhi