

AMENDMENT NO. 1 NOVEMBER 2024
TO
IS 550 (PART 2) : 2021 SAFES
PART 2 TESTS FOR BURGLARY RESISTANCE
(Sixth Revision)

(Page 3, clause 6.4.4.2) — Substitute ‘Class E, C, CC and CCC safes shall be able to resist making a 39 cm² opening (see 3.1) entirely through the door or any face.’ for ‘Class C, CC and CCC safes shall be able to resist making a 39 cm² opening (see 3.1) entirely through the door or any face.’

(Page 4, Table 1) — Substitute the following for the existing:

Table 1 Criteria for Acceptance

(Clauses 6.1.4 and 7)

Sl No.	Class	Classification	Testing on		Criteria			Minimum Net Working Time in min
			Door	Body	Test Method	Test Tools	Opening cm ²	
					Clause Reference			
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
i)	E	TL10 × 6 – FR 30	Yes	Yes	6.4.1 to 6.4.5 and 6.4.9	6.3.3	39	10
ii)	D	Deposit safe (DEP 15D)	Yes	No	6.4.1 to 6.4.6	6.3.2		15
iii)	C	TL-30 (D) × TL - 10 × 5 – FR 30	Yes No	No Yes	6.4.1 to 6.4.5 and 6.4.9	6.3.3		30 10
iv)	CC	TL-15 × 6 – FR 30	No	Yes	6.4.1 to 6.4.5 and 6.4.9	6.3.3		15
v)	CCC	TL-30 × 6 – FR 30	Yes	Yes	6.4.1 to 6.4.5 and 6.4.9	6.3.3		30
vi)	BB	TRTL – 15 × 6	Yes	Yes	6.4.1 to 6.4.7 and 6.4.9 excluding 6.4.6	6.3.5	13	15
vii)	A	TRTL – 30 × 6	Yes	Yes	6.4.1 to 6.4.7 and 6.4.9 excluding 6.4.6	6.3.5		30
viii)	A+	TRTL – 45 × 6	Yes	Yes	6.4.1 to 6.4.7 and 6.4.9 excluding 6.4.6	6.3.5		45
ix)	AA	TRTL – 60 × 6	Yes	Yes	6.4.1 to 6.4.7 and 6.4.9 excluding 6.4.6	6.3.5		60
x)	AAA	TRTL – 90 × 6	Yes	Yes	6.4.1 to 6.4.7 and 6.4.9 excluding 6.4.6	6.3.5		90
xi)	X	TXTL – 60 × 6	Yes	Yes	6.4.1 to 6.4.9 excluding 6.4.6	6.3.3 and 6.3.6		60

NOTE — For those classifications that allow the use of a cutting torch, the quantity of gas consumed in any one test shall be limited to 28 m³ combined oxygen and acetylene gas.

(MED 24)

Price Group 1
Publication, BIS, New Delhi