

**AMENDMENT NO. 1 MAY 1998
TO
IS 13908 : 1993 AIRCRAFT UNIT LOAD DEVICES —
LOADING AND SECURING CARGO — GUIDELINES**

[*Page 2, clause 6.1.1 (c)*] — Substitute the following for the existing:

- ‘c) The top surface of the pallet edge rail shall not be more than 32 mm above the conveying surface when in the loaded condition.’

(*Page 2, clause 6.3.5*) — Insert the following matter at the end:

‘Alternately, flexible doors can be used for containers in view of flexibility, tightness and avoidance of door closing which can occur due to door panel distortion.

Flexible doors are made of highly tear-resistant plastic fabric stiffened by hollow square of section extrusions and steel wire cables. The steel wire cables support the door diagonally across the door area. Locks are inserted into the stiffener at the lower end. There shall be no damage to diagonal cables or attaching hardware.

Flexible doors shall be examined for the following:

- 1) Door cover — There shall be no holes or cuts in the fabric.
- 2) Door stiffener beam:
 - a) There shall be no holes or cracks on the door stiffener,
 - b) Maximum deformation must not exceed the container outside section; and
 - c) Latch bolt or lock pin or any of their attaching rivet shall not be missing or defective.

(HMD 13)