

AMENDMENT NO. 1 FEBRUARY 2020
TO
IS 13962 : 2018/ISO 10317 : 2008 ROLLING BEARINGS — TAPERED ROLLER
BEARINGS — DESIGNATION SYSTEM








(First Revision)

This Amendment no. 1 is identical to Amendment no. 1 : 2013 Design variant designation and comparison of tolerance class designations for single-row tapered roller bearings to ISO 10317 : 2008 issued by International Organisation for Standardisation.

Page 4, Clause 9, Table 2

Replace Table 2 with the following new table:


Table 2 — Design variant designation

Symbol	Designated item	
None	Single-row bearing	
R	Single-row bearing with flanged outer ring	
DZ	Double-row bearing comprising two single inner subunits and a double outer ring with lubrication groove and holes	
DZU	Double-row bearing comprising two single inner subunits and a double outer ring without lubrication groove and/or holes	
Da	Double-row bearing comprising two single inner subunits, an inner ring spacer and a double outer ring with lubrication groove and holes	
DU ^a	Double-row bearing comprising two single inner subunits, an inner ring spacer and a double outer ring without lubrication groove and/or holes	
DB	Back-to-back matched pair of tapered roller bearings comprising two single-row bearings, an inner ring spacer and an outer ring spacer with lubrication groove and holes	

Price Group ...

Amendment No. 1 to IS 13962 : 2018/ISO 10317 : 2008

Table 2 (continued)

Symbol	Designated item	
DBU	Back-to-back matched pair of tapered roller bearings comprising two single-row bearings, an inner ring spacer and an outer ring spacer without lubrication groove and/or holes	
^a	To be used with the prefix L for a separate double outer ring. Double outer rings for D and DU are common to those for DZ and DZU, respectively.	

Page 5

Add the following new Annex A following Clause 12.

Annex A

(informative)

Comparison of tolerance class designations for single-row tapered roller bearings

This annex gives a comparison table of alternative tolerance class designations for single-row tapered roller bearings as defined in ISO 492.

Tolerances for double-row bearings are not defined in ISO 492. For this reason, it is not possible to apply the comparison table to double-row tapered roller bearings.

Table A.1 shows the relationship between the ISO tolerance classes of ISO 492 and tolerance class designations as given in Table 3 (of this International Standard), as well as the tolerance class designations as given in ANSI/ABMA 19.1.

Table A.1 — Tolerance class designation for single-row tapered roller bearings

Symbol in this International Standard (ISO 10317)^a	Tolerance class in accordance with ISO 492^b	ANSI/ABMA 19.1 letter symbol
None	Normal class	K
/P6X	Class 6X	N
/P5	Class 5	C
/P4	Class 4	B
/P2	Class 2	A
^a	“/” may be omitted.	
^b	The tolerances of double-row bearing are not specified in ISO 492.	

Page 5

Add the following new Bibliography following new Annex A:

Bibliography

- [1] ANSI/ABMA 19.1, *Tapered Roller Bearings — Radial — Metric Design*