

**AMENDMENT NO. 2 MARCH 2008
TO
IS 14181 (PART 1) : 2002 SYNTHETIC (PLASTIC)
SLIDE FASTENERS — SPECIAL PURPOSE
PART 1 SPECIFICATION, SELECTION AND ORDERING
GUIDELINE OF THE PRODUCT**

(First Revision)

(Page 3, clause 4.1.7) — Substitute the following for the existing:

‘A movable part consisting essentially of a slider body, puller and spring for locking (wherever applicable), which is used for opening or closing the fastener by separating or engaging the two textile stringers, is called slider. The slider incorporated with a locking device by means of a flat spring, placed on slider body (*see* Fig. 2C), is called flat autolock slider (3 piece type). The slider without any type of locking device is called non-lock slider (*see* Fig. 2A). The slider shall be made of industrial grade plastic. The plastic sliders are light weight, smooth, corrosion-free and resistant to acid/alkali. The plastic being a bad conductor of both heat and electricity would be safe in all environments and more comfortable in extreme cold/hot climates as well as protection from static charge generation in high altitude and EMZ. Another advantage is that plastic sliders may not require painting (to achieve matching shade with textile tape) and therefore paint peel-off and discoloration can be avoided which is critical for most applications. Also such sliders will make slide fasteners environment-friendly due to recyclable plastics. Further, the plastic slider as compared with metal exerts much lesser abrasion on the polyester chain/tape/sewing thread, and therefore the life and durability of garments/end product improves appreciably.’

(Page 3, clause 4.1.7.1) — Substitute the following for the existing:

‘A device incorporated in the slider which restricts undesirable free movement of the slider along the fastener length in an opening direction. Most of the applications of special purpose slide fasteners (L-type) are with flat autolock sliders for use in uniforms and occupational clothing’s/equipments etc. The flat autolock type slider is made of 3 pieces; Body, Puller and Spring (*see* Fig. 2C). The locking device operates automatically by virtue of a spring mechanism placed flat at the top of the slider. The flat autolock sliders are sturdy with minimum number of components and due to its flatness at the top, unique design,

Amend No. 2 to IS 14181 (Part 1) : 2002

mechanism and shape, the flat autolock sliders are stronger, durable and extremely safe and are therefore most ideal for occupational clothing's and equipments, service uniforms, trousers etc. There are other types of locking for slider, such as (i) Conventional Auto Lock Type with 4/5 pieces (*see* Fig. 2B); which is lesser in strength and durability and hence not reliable and safe; and [(ii) Pin Lock type (*see* Fig. 2D)], which works manually and can get unlocked accidentally. It also causes damage to chain and hurts the user, and hence not safe and reliable. Therefore other types of autolock or pin lock type sliders are not suitable for occupational clothing's and equipments, uniforms etc.'

(Page 3, clause 4.1.7.2, last line) — Delete 'Generally pullers shall be rectangular in shape with (or) without a taper at pulling end'.

(Page 6, clause 7.2) — Substitute the following for the existing:

'The sliders, except for spring, shall be made from suitable industrial grade plastics to withstand rigorous and long life of fasteners. The spring shall be made of spring steel or non-corrosive material. If required by the purchaser, the slider can be either painted or provided with special coatings/finish.'

(Page 10, clause 11.5) — Insert the following new clause after clause 11.5:

'11.6 The special purpose (L-Type) plastic slide fasteners having all the parts and components made of industrial plastics, are light weight, resistant to acid/alkali, corrosion free, environmental friendly (as all materials are recyclable) and are safe and durable. Also it is extremely comfortable in hot/cold weather and high altitudes. Plastic sliders (compared with metal) exert much less abrasion over the Polyester chain /tape and therefore ensure improvement in life and durability of product/garment/end stores. The 'Flat Auto Lock Sliders' (made of plastics) are sturdy and have minimum number of components and therefore very reliable and hence ideally suitable for synthetic (Plastic) slide fasteners, special purpose described in this standard.'

[Page 11, Table 7, col 5, Sl No. (ii)] — Substitute 'Non-lock or flat autolock' for 'Non-lock or autolock'.

[Page 11, Table 7, col 5, Sl No. (iii)] — Substitute 'Flat autolock' for 'Autolock'.

[Page 11, Table 7, col 5, Sl No. (viii)] —Substitute 'Flat autolock' for 'Autolock'.

Amend No. 2 to IS 14181 (Part 1) : 2002

[Page 12, clause 13.1, Example (c)] — Substitute following for the existing:

‘Synthetic (or) Plastic, Slide Fasteners — Special purpose — (IS 14181) — Medium Special, Two-way Closed End-Type E, Flat Autolock, OG, 75 cm.’