

AMENDMENT NO. 4 APRIL 2007
TO
IS 1785 (PART 1) : 1983 SPECIFICATION FOR
PLAIN HARD-DRAWN STEEL WIRE FOR
PRESTRESSED CONCRETE

PART 1 COLD DRAWN STRESS-RELIEVED WIRE

(Second Revision)

[Page 5, clause 5.1 (see also Amendment No. 3)] — Insert the following values of *Nominal Diameters* and its corresponding values of *Tolerances*:

<i>Nominal Diameter</i> mm	<i>Tolerance</i> mm
3.00	±0.04
2.50	±0.025

[Page 5, clause 5.1.2 (see also Amendments No. 2 and 3)] — Insert the following values of *Nominal Diameter* and its corresponding values of *Nominal Mass* and *Tolerance* in the existing clause:

<i>Nominal Diameter</i> mm	<i>Nominal Mass</i> g/m	<i>Tolerance</i> g/m
3.00	55.5	±1.5
2.50	38.5	±1.25

[Page 6, clause 6.1 (see also Amendment No. 3)] — Insert the following values of *Nominal Diameter* and its corresponding values of *Tensile Strength* in the existing clause:

<i>Nominal Diameter</i> mm	<i>Tensile Strength, Min</i> N/mm ²
2.50	2 010
3.00	1 865

[Page 6, clause 6.4 (see also Amendment No. 3)] — Insert the following values of *Nominal Diameter* and its corresponding values of *Elongation, Percent* in the existing clause:

Amend No. 4 to IS 1785 (Part 1) : 1983

<i>Nominal Diameter</i> mm	<i>Elongation, Percent</i> <i>Min</i>
2.50	2.5
3.00	2.5

[Page 8, clause 7.5 (see also Amendment No. 3)] — Insert the following values of *Diameter of Wire* and its corresponding values of *Radius of Jaws* in Table 1 under the existing clause:

<i>Diameter of Wire</i> mm	<i>Radius of Jaws</i> mm
2.50	7.50
3.00	10.00

(CED 54)