

**AMENDMENT NO. 3    APRIL    1997**  
**TO**  
**IS 1785 ( Part 2 ) : 1983    SPECIFICATION FOR PLAIN**  
**HARD DRAWN STEEL WIRE FOR PRESTRESSED**  
**CONCRETE**

**PART 2 AS-DRAWN WIRE**

*( First Revision )*

[ *Page 6, clause 5.1.2 ( see also Amendment No. 2 )* ] — Delete in Amendment No. 2 the following values of Nominal Diameter and their corresponding values of Nominal Mass and Tolerance:

| <i>Nominal Diameter</i> | <i>Nominal Mass</i> | <i>Tolerance</i> |
|-------------------------|---------------------|------------------|
| mm                      | g/m                 | g/m              |
| 8.00                    | 395                 | ± 5.9            |
| 7.00                    | 302                 | ± 4.3            |

( *Page 5, clause 3.1.1, line 3* ) — Substitute the following for existing matter:

‘0.040 percent of sulphur’ and ‘not more than 0.040 percent of phosphorus’.

| ( *Page 5, clause 5.1* ) — Insert the following in the existing clause:

| <i>Nominal Dia</i> | <i>Tolerance</i> |
|--------------------|------------------|
| 2.50 mm            | ± 0.02 mm        |

( *Page 6, clause 6.1* ) — Insert the following in the existing clause:

| <i>Nominal Diameter</i> | <i>Tensile Strength, Min</i> |
|-------------------------|------------------------------|
| mm                      | N/mm <sup>2</sup>            |
| 2.50                    | 1 800                        |

( *Page 7, clause 7.5.1, Table 1* ) — Insert the following in the beginning:

| <i>DIAMETER OF WIRE</i> | <i>RADIUS OF JAWS</i> |
|-------------------------|-----------------------|
| mm                      | mm                    |
| 2.50                    | 7.5                   |

( CED 54 )