

**AMENDMENT NO. 1 JUNE 2026**  
**TO**  
**IS 4246 : 2025 DOMESTIC GAS STOVE AND BUILT IN HOB FOR**  
**USE WITH LPG — SPECIFICATION**  
*( Sixth Revision )*

[Foreword, para 3, Sl No. (g)] — Substitute the following for the existing:

‘g) Clause **14** (gas inlet connections) and **26** (thermal efficiency test) have been modified; and’

[Page 1, clause **5.1.1(f)(1)**] — Substitute the following for the existing:

‘1) *Bati/Tandoor*/inverted vessel or similar utensils to be used only with the *Bati* stand with the glass top gas stove/built in hob;’

(Page 3, clause **10**) — Insert the following at the end:

‘**10.1** Injector jet shall be made of metal, with or without ceramic tip. The melting point of the metal shall not be less than 650 °C.

**10.2** The size of the jet in litres/h of flow of LPG at STP conditions shall be impressed on jet.’

(Page 4, clause **14.1**) — Delete.

(Page 5, clause **17.1.2**) — Insert the following at the end:

‘**17.1.3** If two or more jets are operated with a single knob, the rating of jet shall be impressed on jet and the total gas consumption per burner shall be declared.

The simmer rating shall also be total gas consumption of jets and shall be in accordance with **17.2.**’

(Page 5, clause **18.1**, sentence 2) — Substitute the following for the existing:

‘Where burner or burners are lighted by auto ignition electric/electronics or by battery flint operated or by a pilot flame, it shall not be possible for gas to be admitted to the main burner without being smoothly ignited.’

(Page 7, clause **28.1**, para 1) — Substitute the following for the existing:

‘**28.1** The appliance shall be accompanied by an instruction card providing the following information and the instructions may also be provided in Braille script:’

(Page 7, clause **29.1**, para 1) — Substitute the following for the existing:

‘**29.1** Each appliance shall be legibly and indelibly marked with the following and the markings may also be provided in Braille script:’

**Price Group 1**

**Amendment No. 1 to IS 4246 : 2025**

(Page 13, Table 1) — Substitute the following for the existing:

**‘Table 1 Aluminium Pans for Thermal Efficiency Test**

(Clauses 25.2 and F-1.2)

| Sl No. | Gas Rate at STP | Pan Diameter (External) | Pan Height (External) | Total Pan Mass with Lid | Mass of Water in Pan | Pan Bottom Thickness | Pan Side Wall Thickness |
|--------|-----------------|-------------------------|-----------------------|-------------------------|----------------------|----------------------|-------------------------|
|        | l/h             | mm<br>± 5 percent       | mm<br>± 5 percent     | g<br>± 5 percent        | kg                   | mm<br>± 0.07 mm      | mm<br>± 0.07 mm         |
| (1)    | (2)             | (3)                     | (4)                   | (5)                     | (6)                  | (7)                  | (8)                     |
| i)     | Up to 40        | 180                     | 100                   | 356                     | 2.0                  | 1.27                 | 1.25                    |
| ii)    | 41 to 50        | 205                     | 110                   | 451                     | 2.8                  | 1.27                 | 1.25                    |
| iii)   | 51 to 60        | 220                     | 120                   | 519                     | 3.7                  | 1.27                 | 1.25                    |
| iv)    | 61 to 70        | 245                     | 130                   | 632                     | 4.8                  | 1.27                 | 1.25                    |
| v)     | 71 to 80        | 260                     | 140                   | 750                     | 6.1                  | 1.27                 | 1.25                    |
| vi)    | 81 to 95        | 285                     | 155                   | 853                     | 7.7                  | 1.27                 | 1.25                    |
| vii)   | 96 to 107       | 295                     | 165                   | 920                     | 9.4                  | 1.27                 | 1.25                    |
| viii)  | 108 to 110      | 308                     | 169                   | 974                     | 9.5                  | 1.27                 | 1.25                    |
| ix)    | 111 to 120      | 325                     | 179                   | 1 061                   | 10.5                 | 1.27                 | 1.25                    |
| x)     | 121 to 130      | 343                     | 189                   | 1 148                   | 11.6                 | 1.27                 | 1.25                    |
| xi)    | 131 to 140      | 360                     | 198                   | 1 236                   | 12.7                 | 1.27                 | 1.25                    |
| xii)   | 141 to 150      | 378                     | 208                   | 1 323                   | 13.9                 | 1.27                 | 1.25                    |

NOTES

**1** The vessel should be cylindrical.

**2** It should consist of flat bottom.

**3** The vessel should contain bright internal bottom finish.

**4** The purity of aluminium vessel should be at least 98 percent of any grade.

(MED 23)

Publication, BIS, New Delhi