

AMENDMENT NO. 1 JANUARY 2000
TO
IS 4460 (PARTS 1 TO 3) : 1995 GEARS — SPUR AND
HELICAL GEARS — CALCULATION OF LOAD CAPACITY

(First Revision)

(Page 4, clause 2, col 1, line 32) — Read 'Z_L'.

(Page 8, clause 3.6) — Substitute the following formula for the existing :

$$Z_E = \sqrt{\frac{1}{\pi \left[\frac{1 - \mu_1^2}{E_1} + \frac{1 - \mu_2^2}{E_2} \right]}}$$

(Page 28, clause B-3, col 2, line 12, Annex B) — Substitute the following formula for the existing:

$$Y_{Fa1(2)} = \frac{6 \left[\frac{h_{Fa1(2)}}{m_n} \right] \cos \alpha_{an1(2)}}{\left[\frac{S_{Fn1(2)}}{m_n} \right]^2 \cos \alpha_n}$$

(Page 29, clause B-3, col 2, line 2, Annex B) — Substitute the following formula for the existing:

$$Y_\beta = 1 - \epsilon_\beta \times \frac{\beta}{120}, \text{ for } Y_\beta = 1 - \epsilon_\beta = \frac{\beta}{120},$$

(Page 29, clause B-3, col 2, line 11, Annex B) — Substitute the following formula for the existing:

$$\sigma_{FO1(2)} = \frac{F_t}{bm_n} Y_{Fa1(2)} Y_{k1(2)} Y_\epsilon Y_\beta$$

BP (LM 13)

Printed at New India Printing Press, Khurja, India