

AMENDMENT NO. 1 SEPTEMBER 2021

TO

IS 15894 : 2018 INSPECTION GAUGES FOR CHECKING TAPER THREADS OF GAS CYLINDERS VALVES AND CYLINDER NECKS — TAPER 1 IN 16 ON DIAMETER — SPECIFICATION

(*First Revision*)

(Page 3, Table 2, row 1, column 12) — Substitute ‘C Sink 90° X Max Dia. at “T” ref. plane’ for ‘Counter 90° X Max Dia KK’.

(Page 16, clause A-3) — Insert the following title of the clause:

‘Standard procedure to inspect external thread’

[Page 16, clause A-3b), last sentence] — Substitute the following for the existing:

‘The difference shall be maximum ME 11 (see Table 11).’

[Page 16, clause A-3e), line 4] — Substitute ‘ $\pm A-3(e)$ ’ for ‘ $\pm A-3(c)$ ’.

[Page 16, clause A-3f), line 3] — Substitute ‘ $R(EXT)L1_{-0.0}^{+A-3(f)}$ ’ for ‘ $R(EXT)L1_{-0}^{+A-3(d)l}$ ’.

[Page 16, clause A-3g), line 3] — Substitute ‘ $R(EXT)L1_{-0.0}^{+A-3(g)}$ ’ for ‘ $R(EXT)L1_{-0}^{+A-3(e)l}$ ’.

(Page 16, clause A-6) — Insert the following title of the clause:

‘Standard procedure to inspect internal thread’

[Page 17, clause A-6b), last sentence] — Substitute the following for the existing:

‘The difference shall be maximum MI 11 (see Table 10).’

[Page 17, clause A-6f), second sentence] — Substitute the following for the existing:

‘The reading on the dial indicator should be $R(\text{INT})L1_{-0.0}^{+A-6(f)}$ (see Table 14 for value) for the purpose of acceptability of meeting the requirement of relative engagement (see 4.5).’

[Page 17, clause A-6g), line 4] — Substitute ‘ $R(\text{INT})L1_{-0.0}^{+A-6(g)}$ ’, for ‘ $R(\text{Int})L1_{-0}^{+A-6(g)}$ ’.