

**AMENDMENT NO. 1 JUNE 2022**

**TO**

**IS 15943 : 2012 AUTOMOTIVE VEHICLES —  
HAND-HOLDS FOR THREE, FOUR AND  
MORE THAN FOUR WHEELED MOTOR  
VEHICLES — SPECIFICATION**

[Page 1, clause 1(c)] — Substitute the following for existing text:

- ‘c) Four wheeled vehicles registered as Transport Vehicles of categories M1 without doors, L7, M2 and M3.’

(Page 1, clause 3.2.1) — Substitute the following for existing text:

**‘3.2.1** Following are the dimensional requirements for vehicles of category L5M, L5N, L7 and four wheelers of category M1 which are without doors, M2 upto GVW 3.5 tonnes and N1 category :

- a) Length of the handhold shall be at least 100 mm to accommodate a hand of passenger;
- b) Clearance between hand-hold(s) and the adjacent part of vehicle body or wall shall be of at least 25 mm;
- c) Cross-sectional area measured at the middle of the length of the hand-holds other than strap shall be between 130 mm<sup>2</sup> and 1 500 mm<sup>2</sup>, enabling passenger to grasp them easily and firmly; and
- d) In case of straps, width measured at the middle of the length of the strap shall be 40 ± 5 mm.’