

AMENDMENT NO. 1 MARCH 2016
TO
IS 5435 : 1987 GENERAL REQUIREMENTS FOR COLD
BITUMINOUS MACADAM MIXING PLANTS

(First Revision)

(Page 6, clause 7.1) — Insert the following at the end:

‘d) Water storage tank with water pumps.

e) Bitumen oil flushing unit.’

(Page 10, clause 12.2) — Substitute ‘Mixer’ for ‘Mixture’.

(Page 10, clause 12.2.5) — Insert the following new clause:

‘12.2.6 The mixer unit be provided with adequate water spraying nozzles for spraying water to dilute emulsion and add some moisture to the aggregates, as and when required to conserve bitumen emulsion and achieve the required consistency of the cold mix.’

(Page 10, clause 13.1) — Insert the following new clauses and renumber the subsequent clauses:

‘13.1.1 Bitumen Emulsion Agitation System

The bitumen emulsion storage tank shall be provided with a tank mounted, electric motorized agitator of suitable capacity to agitate/churning of bitumen emulsion during storage heating to reduce skin formation and sedimentation.

13.1.2 Bitumen Emulsion Heating Unit

The bitumen emulsion storage tank shall have a suitable electric heating element system with built in temperature gauge, thermo-couple and a timer for heating of bitumen emulsion during storage to maintain it in proper form.

14 BITUMEN EMULSION FLUSHING UNIT

The Mixer shall be provided with oil flushing unit with built in flushing pump, tank of adequate capacity to flush the bitumen spray nozzles, pipe line and pug mill whenever mixing stopped for avoiding chocking of nozzles and bitumen lines.’

(MED 18)