

AMENDMENT NO. 1 JULY 1990
TO
IS : 1038 - 1983 SPECIFICATION FOR STEEL
DOORS, WINDOWS AND VENTILATORS

(Third Revision)

(Page 3, clause 0.2, line 1) — Substitute 'revised in 1968 and 1975' for 'revised in 1968'.

[Page 4, clause 0.4 (j)] — Substitute the following for the existing clause:

'Sub-dividing bar shall be T2 and glazing bar shall be T6 in 15 module or more height for fixed lights only.'

(Page 4, clause 0.6) — Insert the following at the end:

'The committee reviewed the size requirements of the standard and to bring in line with the timber doors and windows, decided to permit non-modular sizes in addition to modular sizes specified at present. The relaxation will be for a period of two years from the publication of this amendment and it is intended that the manufacturing and consumer organizations can gradually switch over within this period to the modular sizes which are the preferred sizes. The size aspect will be reviewed thereafter.'

(Page 5, clause 4.1) — Insert the following at the end:

'Sizes other than modular sizes, as agreed to between the manufacturer and the purchaser, may also be permitted.'

(Page 12, clause 5.2.1, lines 1 and 2) — Substitute 'K11B' for 'K11B' and 'K12B' as transom' for 'K12B'.

(Page 22, clause 6.1 last sentence) — Substitute the following for the existing last sentence:

'The process of welding adopted may be flash butt welding or metal arc welding or any other suitable method. The weld shall fulfil the requirements given in 6.1.1, 6.1.1.1, 6.1.1.2 and 6.1.1.3.'

(Page 22, clause 6.1.1.2) — Substitute the following for the existing clause:

'*Micro and Macro examinations* — From the two opposite corners obtained for visual test as in 6.1.1.1, the flanges of the sections shall be cut with the help of a saw. The cut surfaces of the remaining portions shall be polished,