

AMENDMENT NO. 1 OCTOBER 1980

TO

**IS:1081-1960 CODE OF PRACTICE FOR FIXING
AND GLAZING OF METAL (STEEL AND ALUMINIUM)
DOORS, WINDOWS AND VENTILATORS**

Alterations

**[Page 4 (page 5 of Reprints), clause 3.1] -
Substitute the following for the existing clause**

**'3.1 Putty - Putty used for glazing metal door,
window and ventilator shall conform to IS:419-
1967.'**

(Page 5 of Reprints, foot-note) - Delete.

**[Page 8 (page 9 of Reprints), clause 6.12,
second and third sentences] - Substitute the
following for the existing sentences:**

**'It is recommended to fix by wood screws into
wooden plugs or filler plugs or rawl plugs
positioned in the concrete. These plugs shall
be set in the concrete when pouring or casting
and shall be set very accurately for fixing
holes in the unit.'**

**[Page 12 (page 13 of Reprints), clause 10.5]
Substitute the following for the existing clause:**

**'10.5 Glass shall be secured by special spring
glazing clips (see IS:1038-1975 regarding number
of clips) which shall be inserted in holes already
provided in steel door, window or ventilators
before applying the front putty.'**

**[Page 12 (page 13 of Reprints), clause 10.6] -
Delete and renumber the subsequent clauses
accordingly.**

(EDC 11)