

AMENDMENT NO. 1 MARCH 1989
TO
IS : 9759 - 1981 GUIDELINES FOR DEWATERING
DURING CONSTRUCTION

(Page 6, clause 4.3.1.5, informal table) — Substitute ' $k \times 10^{-4}$ ' for ' k '.

(Page 12, clause 6.3.4.5) — Substitute ' V ' for ' v ' appearing for vacuum at pump intake.

(Page 27, clause B-1.10) — Substitute ' $\frac{N_e}{N_t}$ ' for ' $\frac{N_e}{N_f}$ ' appearing at two places.

(Page 30, Table 2, col 3) — Substitute the following for the value of ' Q ' in lines 1, 2 and 4 respectively:

a) $\frac{kDx}{L} (H - h_e)$

b) $\frac{kx}{2L} (H^3 - h_e^3)$

c) $\left(0.73 + 0.27 \frac{H - h_e}{H} \right) \frac{kx}{2L} (H^3 - h_o^3)$

[Page 30, Table 2, Notes (i) and (ii)] — Substitute ' $H - h_o$ ' for ' $H - h_e$ ' appearing at two places.

(Page 31, Table 3, col 3, line 2) — Substitute the following for the value of ' Q ':

$$\left(0.73 + 0.27 \frac{H - h_e}{H} \right) \frac{kx}{L} (H^3 - h_o^3)$$

(Page 31, Table 3, Note) — Substitute the following for the value of ' h ':

$$h_e + (H - h_e) \frac{J + D}{L + D}$$

(Page 32, Table 4, last line) — Substitute ' h_o ' for ' h_e ' appearing at two places.

(Page 32, Table 5, col 3) — Substitute ' kD_b ' for ' kD_a '.

(Page 33, Table 6, col 3) — Substitute the following value of 'Qw' against ' Gravity ':

$$= \frac{k\pi [(H-S)^2 - t^2]}{\ln(R/rw)} \left[1 + \left(0.3 + \frac{10rw}{H} \right) \sin \frac{1.8S}{H} \right]$$

(Page 33, Table 6, col 3) — Substitute the following against the value of ' Qwp ':

$$\frac{2\pi kD (H - hw) G}{\ln(R/rw)}$$

(Page 33, Table 6, Note) — Substitute the following for the value of ' G ':

$$\frac{W}{D} (1 + \gamma) \sqrt{\frac{rw}{2W} \cos \pi \frac{W/D}{2}}$$

(BDC 43)