

**AMENDMENT NO. 1 NOVEMBER 2005
TO
IS 9780 : 1992 GLASS BOTTLES FOR TOMATO
KETCHUP — SPECIFICATION**

(First Revision)

(Page 1, clause 2) — Substitute the following for the existing clause

2 REFERENCES

The following standards contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below

<i>IS No</i>	<i>Title</i>
2303 (Part 1/ Sec 1) 1994	Grading glass for alkalinity Part 1 Hydrolytic resistance. Section 1 Hydrolytic resistance of glass grains at 98°C — Method of test and classification (<i>first revision</i>)
6654 1992	Glass containers — Glossary of terms (<i>second revision</i>)
6945 1973	Code of practice for packaging glass and glassware
7511 (Part 6) 1986	Dimensions for neck finishes Part 6 Dual neck finish (<i>first revision</i>)
7511 (Part 8) 1986	Dimensions for neck finishes Part 8 Vacuum lug finish (<i>first revision</i>)
10497 1983	Method of test for the determination of brimful capacity of glass containers by gravimetric method
11930 : 1986	Methods of thermal shock tests for glass containers

(Page 1, clause 3.1, second line) — Substitute 'IS 6654' for 'IS 6654 1982'

Amend No. 1 to IS 9780 : 1992

(Page 2, clause 6.1.3) — Substitute the following for the existing clause

‘6.1.3 Limit of Alkalinity

The glass of the bottles shall conform to Class HGB 3 of the glass when graded according to the method prescribed in IS 2303 (Part 1/ Sec 1) ’

(Page 3, clause 6.5.3) — Insert the following at the end

‘6.6 Bottle Washing

All bottles shall be thoroughly cleaned immediately before filling by automatic/semi-automatic washing machines. Washing shall be accomplished by pre-rinse and final rinse. For final rinse dechlorinated potable water shall be used. Bottles should be thoroughly drained, sterilized and dried after final rinse so that strength and purity of content is not affected after filling. Water jets in the washing machine should be so designed and jet pressure so maintained as to thoroughly rinse the whole internal and external surface area of the bottles. Wash water in the bottle washer should be thoroughly drained and changed frequently to prevent algal growth.

6.6.1 Wherever second hand bottles are being used, all the bottles should be pre-washed prior to feeding to the bottle washer. This should be done in the following manner:

- a) Pre-rinse first soaking in a tank to remove labels and other extraneous matter
- b) Rinse in the second tank with hot water around 60°C and 3 percent caustic solution at 60°C using brushes to clean the interior and exterior of bottles thoroughly
- c) Final rinse in the third tank with potable water
- d) Feed the bottles to bottle washer ’

(CHD 10)