

**AMENDMENT NO. 1 DECEMBER 2012
TO
IS 14272 : 2011 AUTOMOTIVE VEHICLES — TYPES —
TERMINOLOGY**

(Page 4, clauses 3.6 and 3.7) — Substitute the following for the existing :

‘3.6 CATEGORY L — Motor vehicles with less than four wheels.

3.6.1 L5 Category — Three-Wheeler — A three wheeled motor vehicle with maximum speed exceeding 25 km and engine capacity exceeding 25 cc, if fitted with a thermic engine, or motor power exceeding 0.25 kW, if fitted with electric motor. This vehicle is normally used for,

- a) carrying persons; or
- b) carrying goods.

Semi-trailer may be attached, and where,

- 1) handle bar or steering wheel may be fitted;
- 2) gross vehicle weight will be limited to 1 500 kg, subject to the conditions given in (4);
- 3) in the case of semi-trailers being attached to a three wheeled tractor, the gross combination weight will be limited to 2 500 kg subject to the conditions given in (4); and
- 4) weight of traction batteries in the case of battery operated three wheelers, shall not be taken into account for the limitation the GVW/ GCW and for the purpose of classification.

3.6.1.1 L5M Category — *Passenger Carrier (Auto-Rickshaw)* — A three-wheeler on account of its technical features intended to carry passengers.

3.6.1.2 L5N Category—*Goods Carrier* — A three wheeler on account of its technical features intended to carry goods.

3.6.1.3 A three-wheeler may fall under the category of L5M [Passenger carrier (Auto-rickshaw)] or L5N (Goods carriage) depending on whether the weight of persons including driver for whom seating arrangements are provided is more than or less than the weight of goods carried.

Amendment No. 1 to IS 14272 : 2011

If the following conditions are satisfied, a three wheeler comes under the category of L5N (Goods carriage) and not L5M [(Passenger carrier (Auto-rickshaw))]:

- a) A separate load body or compartment is provided for carrying the goods;
- b) Number of seating positions excluding the driver is not more than three; and
- c) Weight of goods carried by the vehicle is more than weight of persons carried, as calculated by following formula:

$$P = (A + B \times 68) > B \times 68$$

where

P = technically permissible maximum laden weight (GVW), in kg;

A = vehicle weight in the Kerb weight condition (as defined in IS 9211) + 68, in kg; and

B = number of seating positions excluding the driver.

NOTE — In the case of electric vehicles, the weight of traction batteries is to be subtracted from the Kerb weight.

3.6.2 Two-Wheeler — A two wheeled motor vehicle with maximum speed exceeding 25 km/h and engine capacity exceeding 25 cc, if fitted with a thermic engine, or motor power exceeding 0.25 kW, if fitted with electric motor.

The seating capacity is limited to two persons. A side car may be attached to a two-wheeler. The seating capacity of the side car will be limited to one person.

3.6.2.1 L1 Category — A two-wheeler with maximum speed not exceeding 45 km/h and engine capacity not exceeding 50 cc, if fitted with a thermic engine or motor power not exceeding 0.5 kW, if fitted with electric motor.

3.6.2.2 L2 Category — A two-wheeler other than L1 category.'

(Page 4, clauses 3.8 and 3.9) — Renumber the clauses as 3.7 and 3.8.

(Page 4, clause 3.9) — Insert the following at the end of the clause:

'3.9 Hybrid Electric Vehicles (HEV) — Vehicle in which 'power train' comprises a combination of two different drive train types:

- a) An internal combustion engine; and

Amendment No. 1 to IS 14272 : 2011

b) One (or several) electric drive train(s).

HEV for the purpose of mechanical propulsion, draws energy from both of the following on-vehicle sources of stored energy/power:

- 1) A consumable fuel; and
- 2) An electrical energy/power storage device (for example battery, capacitor, flywheel/ generator.'

(TED 6)