

AMENDMENT NO. 1 JUNE 2011
TO
IS 14593 : 1998 DESIGN AND CONSTRUCTION OF BORED CAST IN-SITU
PILES FOUNDED ON ROCKS — GUIDELINES

[Page 3, clause 6.5.1.1(a), line 18] — Substitute 'side' for 'slide'.

(Page 3, Fig. 2) — Substitute:

$$\begin{array}{ccc} \text{'MODULUS REDUCTION FACTOR,} & & \text{'MASS REDUCTION FACTOR,} \\ i = \frac{E_d}{E_r}, & \text{for} & i = \frac{E_d}{E_i}, \end{array}$$

[Page 3, clause 6.5.1.1(a), para 2, line 2] — Substitute 'modulus reduction' for 'mass'.

(Page 5, clause 6.6.3, line 10) — Substitute:

' l_r = influence factor as given in Fig. 4

$$= \frac{E_p}{E_{ds}}$$

where

$$\begin{array}{ll} E_p & = \text{modulus of pile material;} \\ E_{ds} & = \text{modulus of rock mass around socket.} \end{array}$$

for

' l_r = influence factor as given in Fig. 4; and'

(Page 5, clause 6.7.3.2, line 8) — Substitute:

' R = relative stiffness factor

$$= \frac{E_p l_p}{E_s l_s^4}$$

Amend No. 1 to IS 14593 : 1998

where

E_p = modulus of pile material;
 E_s = modulus of soil;
 I_p = moment of inertia of pile; and
 l_s = length of socket.

for

‘ R = relative stiffness factor as per IS 2911 (Part 1/Sec 2)’.

(Page 7, clause 7, line 2) — Substitute ‘manufacture’ *for* ‘manufacturer’.

(CED 48)

Reprography Unit, BIS, New Delhi, India