

AMENDMENT NO. 2 JULY 2019
TO
IS 14664 : 2010 AUTOMOTIVE VEHICLES —
PERFORMANCE REQUIREMENTS AND TESTING
PROCEDURE FOR BRAKING SYSTEM OF TWO AND
THREE WHEELED MOTOR VEHICLES

(First Revision)

(Page 4, clause 4.2.2) — Substitute the following for the existing :

‘4.2.2 The friction material thickness shall either be visible without disassembly of brakes, or where the friction material is not visible; wear shall be assessed by means of a device designed for that purpose or it shall be possible to easily check this by utilizing the tools or equipment normally supplied with the vehicle.’

(Page 7, clause 5.3.2) — Substitute the following for the existing :

‘5.3.2 *Test Conditions and Procedure*

a) Initial brake temperature: $\geq 55^{\circ}\text{C}$ and $\leq 100^{\circ}\text{C}$;

b) Test speed:

1) Vehicle categories 3-1 and 3-2: 40 km/h or $0.9 V_{\text{Max}}$, whichever is lower;
and

2) Vehicle categories 3-3, 3-4 and 3-5: 60 km/h or $0.9 V_{\text{Max}}$, whichever is lower.

c) Brake application:

Each service brake system control actuated separately;

d) Brake actuation force:

1) Hand control : $\leq 200\text{ N}$; and

2) Manual control : $\leq 400\text{ N}$ in case of hand operated parking brake.

3) Foot control : $\leq 350\text{ N}$ for vehicle categories 3-1, 3-2, 3-3 and 3-4 $\leq 500\text{ N}$ for vehicle category 3-5.

e) Number of stops : Until the vehicle meets the performance requirements, with a maximum of 6 stops; and

f) For each stop, accelerate the vehicle to the test speed and then actuate the brake control under the conditions specified in 5.3.2’

Amendment No. 2 to IS 14664 : 2010

[Page 17, clause **5.13.3** (see also Amendment No. 1)] — Substitute the following for the existing:

‘5.13.3 Performance requirements

When the brakes are tested in accordance with the test procedure set out in **5.13.2**, the stopping distance shall be as specified in column 2 or the MFDD shall be as specified in col 3 of the Table 4.’

[Page 24, Table 4 (see also Amendment No. 1)] — Substitute the following for the existing heading:

‘Table 4 Performance Requirements of Braking System (Clause 5.13.3)’