

AMENDMENT NO. 3 DECEMBER 2019

TO

IS 14664 : 2010 AUTOMOTIVE VEHICLES — PERFORMANCE REQUIREMENTS AND TESTING PROCEDURE FOR BRAKING SYSTEM OF TWO AND THREE WHEELED MOTOR VEHICLES

(*First Revision*)

(Page 6, clause 5.1.6) — Substitute the following for the existing clause:

‘5.1.6 Vehicle Position and Wheel Lock

- a) Vehicle is positioned in the centre of the test lane for the beginning of each stop; and
- b) Stops are made without the vehicle wheels passing outside the applicable test lane and without wheel lock. However, wheel locking towards the end of the stop in last one meter shall be permitted.’

(Page 8, clause 5.4.3) — Substitute the following for the existing clause:

‘5.4.3 Performance Requirements

When the brakes are tested in accordance with the test procedure set out in 5.4.2, the stopping distance (S) shall be,

- a) for vehicle categories 3-3 and 3-4: $S \leq 0.0060 V^2$; and
- b) for vehicle category 3-5: $S \leq 0.1 V + 0.0060 V^2$.

where

V = specified test speed, in km/h, and S is the required stopping distance in metres.

NOTE — For vehicles with CBS or split service brake systems for laden and lightly loaded conditions, if the stopping distance requirement for compliance with those specified in Table 1 is more stringent than requirement specified above, this test need not be carried out.’

[Page 24, Table 3, Sl No. vii], col (2)] — Substitute following for the existing:

‘Any decrease in wheel base by more than 10 percent’