

AMENDMENT NO. 1 DECEMBER 2000
TO
IS 14683 : 1999 AGRICULTURAL TRACTORS AND
MACHINERY — LIGHTING DEVICES FOR TRAVEL ON
PUBLIC ROADS

(*Page 2, clause 4.1.2, last sentence*) — Insert the following at the end:

‘If the structure of the vehicle makes it impossible to maintain this maximum height (that is 1 600 mm), the height of warning lamps may be raised to 1800 mm.’

(*Page 2, clause 4.1.3*) — Substitute the following for the existing text:

‘At least two amber flashing warning lamps conforming to IS 4060 or 13135 symmetrically mounted and as widely spaced laterally as practicable, visible from both front and rear, mounted at least 1 000 mm height but not more than 1 500 mm. If the structure of the vehicle makes it impossible to maintain this maximum height (that is 1 500 mm), the height of warning lamps may be raised to 1 800 mm. Lamps shall flash in unison at a rate of 60 to 120 flashes per minute.’

(*Page 3, clause 4.1.8, last sentence*) — Substitute the following for the existing sentence:

‘The parking lights can also be mounted on the mudguards at a height not exceeding 1 600 mm. If the structure of the vehicle makes it impossible to maintain this maximum height (that is 1 600 mm), the height of parking light may be raised to 1 800 mm.’

(FAD 32)