

**AMENDMENT NO. 2 JULY 2006  
TO  
IS 14683 : 1999 AGRICULTURAL TRACTORS AND  
MACHINERY — LIGHTING DEVICES FOR TRAVEL ON  
PUBLIC ROADS**

( *Page 2, clause 4.1.2* ) — Substitute the following for the existing text:

‘Every tractor shall be provided with two tail lights of red colour conforming to IS 3628. The point on the illuminating surface farthest from the median longitudinal plane of tractor shall not be more than 500 mm from the extreme outer edge of the vehicle. This distance between the inner edge of the two illuminating surfaces shall not be less than 500 mm. The distance may be reduced to 400 mm, where the overall width of the vehicle is less than 1 400 mm. The height of tail lights above the ground shall not be less than 350 mm and not more than 2 100 mm.’

( *Page 3, clause 4.1.4.2* ) — Substitute the following for the existing text:

The height of turn indicators on the front side shall be between 500 mm to 1 600 mm. If structure of vehicle makes it impossible to keep the figure, that is 1 600 mm, height of turn indicators may be raised to 2 100 mm.

( *Page 3, Fig. 2* ) — Substitute the value of upper limit of trailer socket above the drawbar to ‘1 500’ (mm) for ‘1 016’ (mm).

( FAD 11 )