

AMENDMENT NO. 1 NOVEMBER 2025
TO
IS 14899 : 2014 LIQUEFIED PETROLEUM GAS (LPG) CONTAINERS FOR
AUTOMOTIVE USE — SPECIFICATION
(First Revision)

(Page 7, clause 10, Table) — Substitute the following for the existing:

<i>Sl No.</i>	<i>Test</i>	<i>Test During Production</i>	<i>Performance Verification Testing</i>	<i>Number of Containers to be Tested</i>	<i>Method of Test, Ref to</i>
(1)	(2)	(3)	(4)	(5)	(6)
i)	Tensile strength test	1 per batch	X ¹⁾	2 ²⁾	10.1.3
ii)	Bend test	1 per batch	X	2 ²⁾	10.1.5
iii)	Burst test	1 per batch	X	2	10.2.2
iv)	Hydrostatic testing	Each container	X	All containers submitted for performance verification	10.3
v)	Pneumatic leakage test	Each container	X	Each container	10.4
vi)	Fatigue test	—	X	3	10.6.2
vii)	Bonfire test	—	X	1	10.6.1
viii)	Radiographic examination of welds	At least 1 per batch	X	100 percent of the container under test	10.5.1
ix)	Macroscopic examination of welds	1 per batch	X	2 ²⁾	10.1.6
x)	Examination of outside surface of weld	Each container	X	Each container	10.5.5
xi)	Visual inspection of container parts	Each container	X	Each container	7.2, 8

During the performance verification testing, on one of the containers to be tested, the volume of the container and the wall thickness of each part of the container shall be determined. The number of test samples for performance verification testing shall be six; they shall be produced consecutively.

NOTE — X = test required.

(Page 7, clause **10.1.4**) — ‘Delete’.

(Page 12, clause **12.1**) — Insert the following at the end:

‘(q) Permanent and tamper proof marking in form of bar code (as approved by statutory authority).

NOTE — ‘Bar Code’ means a machine readable graphical picture having alphabet, character, number embedded in it and includes radio frequency identification or quick response code.’

¹⁾ Test required.

²⁾ These test pieces can be taken from one container.