

AMENDMENT NO. 1 APRIL 1977
TO
IS : 7073 (Part I)-1973 GLOSSARY OF
TERMS RELATING TO AIR CARGO
PALLETS AND CONTAINERS

PART I AIR CARGO PALLETS

Alterations

(*First cover page, pages 1 to 7, Designation*)— Substitute 'IS : 7073-1973'
for ' IS : 7073 (Part I)-1973 '.

(*First cover page, pages 1 and 3*)— Substitute the following for the
existing title:

'Indian Standard
GLOSSARY OF
TERMS RELATING TO AIR CARGO
PALLETS AND CONTAINERS'

(*Page 3, clause 0.2*) — Delete the existing clause and re-number
clause '**0.3**' as '**0.2**'.

(*Page 3, clause 1.1*) — Substitute the following for the existing
clause:

' **1.1** This standard covers basic terms relating to air cargo pallets and
containers.'

Addenda

(*Page 7, clause 2.50*) — Add the following new terms after
clause **2.50**:

2.51 Base — It is the bottom of a container, that may sometimes be a
pallet which comes in contact with the floor.

2.52 Carriage — It is equivalent to the term transportation, means
carriage of goods by air on an airport-to-airport basis, including
all services of the carrier incidental thereto.

2.53 Container — It is a receptacle used to group individual items or
packages into a single larger unit load.

2.54 Contour — It is a contoured container, one which is specifically designed to aircraft loading contours in order to utilize the maximum cubic space available in aircraft cabins or holds, subject to practical loading limitations.

2.55 Cross-Section — The constant cross-section is the internal contour of aircraft measured in a plane perpendicular to the aircraft length and excludes any tapered section of the fuselage.

2.56 Deflection — The changes in shape (bulge) of a sidewall or panel of a container or igloo (or component parts thereof) when subjected to compression loads.

2.57 Distortion — The permanent bulge or bowing of a panel beyond its original shape.

2.58 Dynamic Load Test — It means that the completely assembled and closed container is positioned on a platform scale and a moving platen is brought into position to apply a continually increasing pressure up to the limit required.

2.59 End — The walls of the container which, when loaded into an aircraft, are fore and aft.

2.60 Fill — To insert (load) goods into or onto a unit load device.

2.61 Fittings — It is in an aircraft, which means the restraint rails and floor locking devices installed to hold the aircraft unit load device. On a unit load device it may mean any supplementary hardware (buckles, rings) on the attachment points on the pallet.

2.62 Floor Bearing — The maximum weight that the aircraft floor is capable of withstanding. The distribution of weight evenly over the aircraft floor to meet weight and balance requirements.

2.63 Fore and Aft — The front and the rear (tail) of an aircraft.

2.64 Forklift Entry — Entries on the base of a container or aircraft unit load device to permit insertion of fork tines in order to move the unit.

2.65 Identification Code — The markings on a unit that indicates the type, size, category, serial number and restraint.

2.66 Inboard Side — The wall of a half size unit which faces into the centre-line of the aircraft.

2.67 Inter-model — Carriage by different modes of transport, that is, rail, truck, sea and air.

2.68 Internal Tiedowns — A means of securing cargo inside a container.

2.69 Markings — The registration markings on a unit load device to indicate the detail characteristics of the unit.

2.70 Non-aircraft Container — A box, either contoured or rectangular, primarily made of fibreboard or plywood but sometimes permanent metal or fibreglass materials, designed to be carried on or in an aircraft unit load device.

2.71 Ratings — For the ratings of containers suitable for air and surface transport, the following definitions shall apply:

- a) *Maximum Gross Mass (R)* — The maximum allowable combined mass of the container and its cargo;
- b) *Tare (T)* — Mass of the empty container, including its normal complement of loading restraint devices; and
- c) *Maximum Payload (P)* — The maximum allowable mass of the cargo equal to the difference between the maximum gross mass and the tare.

2.72 Side (of a Container) — The walls of a container which, when loaded in an aircraft, face the port or starboard wall of the fuselage.

2.73 Stacking — Placing one unit on top of another, or in multiples, either in a warehouse or in an aircraft, for purposes of saving floor space.

2.74 Unloading — Removing loaded aircraft unit load devices or bulk cargo from an aircraft.

2.75 Volume — The cubic capacity of a unit based on the external (or internal) dimensions.

2.76 Wall Deflection — Horizontal bulge of a container wall under compression.

2.77 Width — In relation to containers, measured across the aircraft.