

AMENDMENT NO. 2 MAY 2019
TO
IS 7079 : 2008 AUTOMOTIVE VEHICLES — BRAKE HOSE
ASSEMBLIES FOR HYDRAULIC BRAKING SYSTEMS
USED WITH NON-PETROLEUM BASE BRAKE FLUID —
SPECIFICATION

(Third Revision)

(Page 1, clause 3.2) — Insert the following new clauses :

‘3.2.1 Type A Hose — Where the hoses are used to cater multi directional relative movements.

3.2.2 Type B Hose — Where the hoses are used to cater one directional relative movement.’

(Page 4, clause 5.8) — Substitute the following for the existing clause:

‘5.8 Whip Test

The minimum life of any one of the sample hose assemblies when tested in accordance with Annex D with free length ranging from 200 to 600 mm for 3.5 mm or less and 200 to 400 mm for 4 to 5 mm bore hoses, run continuously on the flexible machine shall be 35 h. This requirement is not applicable for Type B hose.

NOTE — If the hose assembly is longer than the above specified length, use the max length indicated in the respective category of col 2 of Table 6.’

(Page 5, clause 5.14) — Substitute the following for the existing clause:

‘5.14 Dynamic Ozone Resistance Test

The outer cover of the hose shall not show cracks visible to the naked eye without magnification when tested in accordance with Annex F at the worst stress condition, ignoring the areas immediately adjacent to or within the area covered by the band clamps. This requirement is not applicable for Type B hose.’

Amendment No. 2 to IS 7079 : 2008

(Page 6, clause A-1.1) — Substitute the following for the existing clause:

‘**A-1.1** Constriction of the bore of the hose ends after swaging shall be measured with a gauge plug as shown in Fig 1. The mass of the gauge plug shall be 57 ± 3 g and diameter A shall be 64 percent, minimum of nominal diameter of the hose for Type A hose and 50 percent, minimum of nominal diameter of hose for Type B hose.’