

3712 370 13/8-16

AMENDMENT NO. 1 AUGUST 2005
TO
IS 7113 : 2003 SOIL-CEMENT LINING FOR
CANALS — CODE OF PRACTICE
(First Revision)

(Foreword, para 5) — Substitute the following for the existing matter:

‘In many areas local soils mixed with water and cement may be used to construct adequate soil-cement linings. Part of cement up to 35 percent by weight may be replaced by flyash. Soil-cement mixtures are relatively dry mixtures of soil-cement or soil-cement flyash and water, compacted to a maximum density. The suitability of the soil and the proportions of the mix to be used should be determined by laboratory tests before any work is undertaken.’

(Page 1, clause 2) — Insert the following after IS 3037 : 1986:

‘IS 3812 (Part 1) : 2003 Specification for pulverized fuel ash, for use as pozzolana in cement, cement mortar and concrete.’

(Page 1, clause 3.1) — Substitute the following for the existing clause:

‘3.1 Soil-Cement Lining — Lining constructed by compacting soil-cement mix, in which up to 35 percent by weight of cement may be replaced by flyash, at optimum moisture content.’

(Page 1, clauses 3.2 and 3.3) — Substitute ‘soil-cement or soil-cement flyash mixture’ for ‘soil-cement mixture’.

[Page 1, clause 4(a)] — Substitute ‘presence’ for ‘presents’.

(Page 2, clause 5.1) — Insert the following subclause after 5.1:

‘5.1.1 Flyash — Flyash shall conform to IS 3812 (Part 1).’

(Page 2, clause 6.2) — Substitute ‘The cement content of the soil-cement mixture or cement and flyash content of the soil-cement flyash mixture’ for ‘The cement content of the soil-cement mixture’.

(Page 3, Table 1) — Substitute the following for the existing title:

‘Permeability Values (Laboratory) of Some Soil-Cement or Soil-Cement Mix’

(Page 3, clause 7.4.3) — Substitute ‘the same soil cement or soil-cement flyash mix’ for ‘The same soil-cement mix’.

7113 : 2003

se 8.2) — Substitute the following for the existing clause:

'8.2 Mixing Soil and Cement or Soil, Cement and Flyash — The required quantity of cement or cement and flyash shall be thoroughly mixed with the dry soil either mechanically or by hand-mixing through manual labour. The mixing shall be continued till the soil-cement or soil-cement flyash mix acquires uniform colouration which can be examined under a magnifying glass. The required quantity of water will be added and mixing continued to ensure uniform distribution of the moisture throughout the soil-cement or soil-cement flyash mass.'

(Page 4, clause 8.2.1) — Substitute 'The appropriate quantities of soil and cement or soil-cement and flyash' for 'The appropriate quantities of soil and cement'.

[Page 5, clause 9(b)] — Substitute the following first sentence for the existing:

'b) *Cementitious Content* — An adequate cement or cement and flyash content is a primary controlling factor deserving maximum attention in the field.'

[Page 5, clause 9(d)] — Substitute the following first sentence for the existing:

'The dry density of the compacted soil cement mix/soil cement and flyash mix shall be measured at intervals of 100 m or as specified by the engineer-in-charge along the length of the canals.'

(WRD 13)