

AMENDMENT NO. 1 JUNE 2024

TO

**IS 7302 : 2018 VALVE FITTINGS FOR SELF CONTAINED BREATHING
APPARATUS (SCBA) AND SELF CONTAINED UNDERWATER BREATHING
APPARATUS (SCUBA) — SPECIFICATION**

(First Revision)

(Page 16, clause 8.1, line 12) — Substitute ‘valve design’ for ‘valve family’.

[Page 16, clause 8.3 (b) line 2, 8.3 (e) line 6, and 8.3 (g) line 4] — Substitute ‘to be decided in consultation with Inspection Authority’ for ‘to be decided case by case’.

[Page 16, clause 8.3 (b), Note] — Substitute the following for the existing:

‘NOTE — It is recognized that change in chemical composition of valve body material from one grade of brass to another grade of brass will not require repeat of the endurance test.’

(Page 18, Table 2A) — Substitute the following for the existing:

Table 2A Recommended Valving Torque for Taper Threaded Valve Stem

(Clauses 8.6.2 and 8.6.3)

Sl No.	Valve Material	Category	Inlet Thread Code	Valving Torque, N-m (Seamless steel cylinders up to 300 bar)	
				Minimum	Maximum
(1)	(2)	(3)	(4)	(5)	(6)
i)	Copper base alloy and Carbon steel	I	18T	120	150
ii)			08N		
iii)			17E		
iv)		II	25.4	200	300
v)			12N		
vi)			25E		
NOTE — The torque figures given above are for use with PTFE thread sealant. If different sealant or pressure ranges are introduced, the torque figures given in the table may have to be changed to ensure a gas tight joint.					

(Page 19, Table 2B) — Substitute the following for the existing:

Table 2B Recommended Valving Torque for Parallel Threaded Valve Stem for Aluminium Cylinder (Type 1, Type 2, Type 3)

(Clauses 8.6.2 and 8.6.3)

Sl No.	Valve Material	Category	Inlet Thread Code	Valving Torque, N-m	
				Minimum	Maximum
(1)	(2)	(3)	(4)	(5)	(6)
i)	Copper base alloy, Carbon steel and Stainless steel	I	18P	85	90
ii)		II	25P	95	130

(Page 19, clause 8.7.1, line 3) — Substitute ‘valve design’ for ‘valve family’.

(MED 16)

Pulication Unit, BIS, New Delhi