

AMENDMENT NO. 4 FEBRUARY 2024
TO
IS 7347 : 1974 SPECIFICATION FOR PERFORMANCE OF SMALL SIZE SPARK
IGNITION ENGINES FOR AGRICULTURAL WATER PUMPS, SPRAYERS,
TILLERS, REAPERS AND OTHER SIMILAR APPLICATIONS

(Page 5, clause 9.8) — Substitute the following for the existing:

9.8 Strip Examination

The engine shall be dismantled and dimensional and physical inspection shall be carried out for components checked during initial examination (*see 8.1*) to find out whether any undue wear has taken place. The wear limit for various components is given below:

<i>Sl No.</i>	<i>Assembly/Sub-assembly/ Component</i>	<i>Sub-component</i>	<i>Characteristic Dimension</i>	<i>Max Wear Limit (mm)</i>
(1)	(2)	(3)	(4)	(5)
i)	Cylinder and cylinder head wear limit	Cylinder liner	Diameter	0.07
ii)	Valve gear	—	Stem diameter	0.6
			Total length	0.3
iii)	Piston assembly	Piston rings	Radial thickness	0.2
			Width (axial thickness)	0.4
			Close gap	0.4
		Piston/Gudgeon pin	Pin diameter	0.05
iv)	Crank shaft journals and bearing	Crank pin	Diameter	0.03
v)	Connecting rod including small end and large end bearing	Small end bush	Bore	0.06
		Big end bearing	Bore	0.06
vi)	Governor spring	—	Length	1.0
			Wire diameter	0.2

(TED 02)

Price Group 1

Publication, BIS, New Delhi