

AMENDMENT NO. 1 AUGUST 2025
TO
IS 16362 : 2024 GEOSYNTHETICS — GEOTEXTILES FOR SUBSURFACE
DRAINAGE, SUBGRADE SEPARATION, SUBGRADE STABILIZATION,
FILTRATION AND EROSION CONTROL (IN HARD ARMOR SYSTEMS)
APPLICATIONS — SPECIFICATION
(Second Revision)

(Page 4, Table 1, heading) — Substitute the following for the existing:

Sl No.	Characteristic	Requirements						Method of Test, Ref to
		Class 1H		Class 2H		Class 3H		
		Strain < 50 percent	Strain ≥ 50 percent	Strain < 50 percent	Strain ≥ 50 percent	Strain < 50 percent	Strain ≥ 50 percent	

[Page 4, Table 1, Sl No. (i)(h), col (2)] — Substitute the following for the existing:

‘Abrasion strength (*see* Note 2), N, *Min*’.

[Page 6, Table 6, Sl No. (ii)(a), col (3) and col (4)] — Substitute ‘0.085’ for ‘0.850’.

[Page 6, Table 6, Sl No. (ii)(b), col (5)] — Substitute ‘IS 14324’ for ‘IS 17179’.

(TXD 30)

Price Group 1
Publication, New Delhi, BIS