

**AMENDMENT NO. 1 AUGUST 2023**  
**TO**  
**IS 16542 : 2016 DIRECT INSERTION TYPE STORAGE WATER TANK FOR ALL**  
**GLASS EVACUATED TUBES SOLAR COLLECTOR — SPECIFICATION**

[Page 2, clause 5.1(b)] — Substitute the following for existing note:

‘NOTE — For purpose of protective coating on mild steel plate Total Dissolved Solids (TDS) considered is ( $\geq 1\,000$  PPM) and chlorides contents ( $\leq 300$  PPM) in water.’

(Page 2, clause 5.2) — Substitute following for existing clause:

**‘5.2 Outer Cladding**

The material of outer cladding shall be pre-painted galvanized steel conforming to IS 14246. Alternatively, material of outer cladding may be aluminum/stainless steel/FRP/aluminum-zinc alloy of suitable thickness.’

(Page 2, clause 5.3) — Substitute following for existing clause:

**‘5.3 Insulation Layer**

The insulation layer shall be pre-injected polyurethane foam (PUF) of minimum thickness 50 mm. The density of PUF shall be 28 kg/m<sup>3</sup> to 36 kg/m<sup>3</sup>. However, if any other material is used, it should conform to clause 7.5.’

(Page 2, clause 7.5) — Substitute ‘< 2.5 W/(m<sup>2</sup> °C)’ for ‘< 2.0 W/(m<sup>2</sup> °C)’.